


| | |
|--|--|
| Switch ALLIED TELESIS AT-GS950/16-50 |  |
| Codice | CK198270 |
| EAN | 0767035178424 |
| Marca | ALLIED TELESIS |
| Part number | AT-GS950/16-50 |
| Storage unit | |
| Unità di vendita | Cadauno |
| Confezione | 1 |
| Imballaggio | 1 |
| Peso (kg) | 2.92 |
| Volume (cm ³) | 8848 |
| <p>WebSmart Switch 16 porte 10/100/1000TX + 2 Porte combo 10/100/1000TX o SFP</p> <p>The Allied Telesis GS950/16 eco-friendly WebSmart switch upholds the Allied Telesis commitment to environmentally friendly processes and products. It is designed to minimize power consumption through the use of a high-efficiency power supply and a low power chipset.</p> <p>The GS950/16 features 16 x 10/100/1000T ports and an additional two Gigabit SFP combo ports. This WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. The AT-GS950/16 provides key features using the simple web-based management function, such as port-based VLANs, IEEE 802.1p QoS, port trunking/link aggregation, port mirroring, priority queues, and IEEE 802.1x security support.</p> | |

| |
|--|
| |
|--|

| SPECIFICHE | |
|------------------|----------------|
| Marca | ALLIED TELESIS |
| Numero porte LAN | 16 n |

| CARATTERISTICHE TECNICHE | |
|----------------------------|---------------------|
| Power over Ethernet (PoE) | No |
| Gestione | Smart Managed (WEB) |
| Supporto Routing (Layer 3) | No |
| Nr. porte PoE | 0 |
| Vlan supportate | 4000 |
| Industriale | No |
| Stackable | No |
| PoE Budget | 0 W |
| Quality Of Service (QOS) | Si |
| Modalità Stacking | No |

| CARATTERISTICHE FISICHE | |
|-------------------------|---------|
| Rack-Mountable | Si |
| Larghezza | 330 mm |
| Nr. unità rack | 0 |
| Profondità | 200 mm |
| Altezza | 44 mm |
| Peso | 2100 gr |

| ALIMENTAZIONE | |
|-------------------------|---------|
| Power Supply | AC |
| Alimentatore incluso | Si |
| Alimentazione ridondata | No |
| Consumo energetico | 14,24 W |

| CONNETTIVITÀ | |
|---------------------------|-------------------|
| Nr. porte LAN | 16 N |
| Tipo e velocità porte LAN | RJ-45 10/100/1000 |
| Nr. porte Uplink | 2 |

| | |
|--|---|
| Tipo e velocità porte Uplink | N/A |
| Porta Console | No |
| Nr. porte fruibili contemporaneamente (LAN + Uplink) | 16 |
| CONFORMITÀ | |
| Dichiarazione di Conformità | UL 1950FCC/EN55022 Class AVCCI Class AC-TickEN60950 (TUV)EN55024CECSA / CUL |