


<b>Switch ALLIED TELESIS AT-GS950/8-50</b>	
Codice	CK198276
EAN	0767035181349
Marca	ALLIED TELESIS
Part number	AT-GS950/8-50
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	2.45
Volume (cm <sup>3</sup> )	9562.5
<p>Switch Allied Telesis websmart managed con 8 porte 10/100/1000T e 2 porte combo SFP.</p> <p><b>WebSmart Gigabit Ethernet Switch</b>          The Allied Telesis GS950/8 eco-friendly WebSmart switch upholds the Allied Telesis commitment to environmentally friendly processes and products. It is designed to minimize power consumption through the use of a high-efficiency power supply and a low power chipset. The GS950/8 features 8 x 10/100/1000T ports and an additional two Gigabit SFP combo ports. This WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. The GS950/16 provides key features using the simple web-based management function, such as port-based VLANs, IEEE 802.1p QoS, port trunking/link aggregation, port mirroring, priority queues, and IEEE 802.1x security support.</p>	

SPECIFICHE	
Marca	ALLIED TELESIS
Numero porte LAN	8 n

ALIMENTAZIONE	
Power Supply	AC
Alimentatore incluso	Si
Consumo energetico	9,7 W
Alimentazione ridondata	No

CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	No
Nr. porte PoE	0
Quality Of Service (QOS)	Si
Supporto Routing (Layer 3)	No
Dimensioni tabella MAC	8000
Vlan supportate	4000
Modalità Stacking	No
PoE Budget	0 W
Gestione	Smart Managed (WEB)
Industriale	No
Stackable	No

CARATTERISTICHE FISICHE	
Altezza	44 mm
Larghezza	280 mm
Peso	1,5 gr
Profondità	180 mm
Rack-Mountable	Si
Nr. unità rack	0

CONFORMITÀ	
Dichiarazione di Conformità	UL 1950FCC/EN55022 Class AVCCI Class AC-TickEN60950 (TUV)EN55024CECSA / CUL

CONNETTIVITÀ	
Porta Console	No
Nr. porte LAN	8 N

Altre informazioni sulla connettività	8 port 10/100/1000T WebSmart switch with 2 SFP combo ports
Nr. porte Uplink	2
Tipo e velocità porte LAN	RJ-45 10/100/1000
Nr. porte fruibili contemporaneamente (LAN + Uplink)	8
Tipo e velocità porte Uplink	N/A