

Switch netgear av line m4250-26g4xf std0000701335



Codice	CK211234
EAN	0606449151619
Marca	NETGEAR
Part number	6315524
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	7.925
Volume (cm ³)	30806.25

24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget

2-port 10/100/1000BASE-T (RJ45)

4-port 1000/10GBASE-X (SFP+)

132 Gbps non-blocking fabric across 30 ports

Out-of-band 1G Ethernet management port

USB-C and RJ45 RS232 console ports and USB-A storage port

Front black display panel and all ports in the back

Possible reversed mounting with ports in the front

Rack-mounting standard brackets

Longer brackets for recessed mounting (2 inches / 5 cm)

Threaded hole in front (1xM10) for clamps

Threaded holes on the bottom (4xM5) for 50x100mm VESA plates

Selectable fan modes for fanless, quiet, or cool operation

Dimensions (WxDxH): 440 x 43.2 x 400 mm

Weight: 5.45Kg (12.02lb)

SPECIFICHE

Marca	NETGEAR
Numero porte LAN	30 n

CARATTERISTICHE TECNICHE

Power over Ethernet (PoE)	Si
Gestione	Layer 2+
Supporto Routing (Layer 3)	No
Nr. porte PoE	24
Vlan supportate	4093
Industriale	No
Stackable	No
PoE Budget	480 W
Attacco su barra DIN	No
Quality Of Service (QOS)	Si
Modalità Stacking	No
Dimensioni tabella MAC	16000
Standard PoE supportati	30W
Altre caratteristiche tecniche	24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000/10GBASE-X (SFP+) 132 Gbps non-blocking fabric across 30 ports Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port

	<p>Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for fanless, quiet, or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 5.45Kg (12.02lb)</p>
Nr. slot	0
CARATTERISTICHE FISICHE	
Rack-Mountable	Si
Larghezza	440 mm
Nr. unità rack	1
Profondità	400 mm
Altezza	44 mm
Peso	545 gr
Altre caratteristiche fisiche	<p>24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000/10GBASE-X (SFP+) 132 Gbps non-blocking fabric across 30 ports Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for fanless, quiet, or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 5.45Kg (12.02lb)</p>
ALIMENTAZIONE	
Power Supply	AC
Alimentatore incluso	Si
Alimentazione ridondata	No
Consumo energetico	614 W
Tipologia di alimentazione ridondata	Nessuna ridondanza di alimentazione

CONNETTIVITÀ	
Nr. porte LAN	30 N
Tipo e velocità porte LAN	RJ-45 10/100/1000
Nr. porte Uplink	4
Tipo e velocità porte Uplink	SFP/SFP+
Porta Console	Si
Altre informazioni sulla connettività	<p>24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget</p> <p>2-port 10/100/1000BASE-T (RJ45)</p> <p>4-port 1000/10GBASE-X (SFP+)</p> <p>132 Gbps non-blocking fabric across 30 ports</p> <p>Out-of-band 1G Ethernet management port</p> <p>USB-C and RJ45 RS232 console ports and USB-A storage port</p> <p>Front black display panel and all ports in the back</p> <p>Possible reversed mounting with ports in the front</p> <p>Rack-mounting standard brackets</p> <p>Longer brackets for recessed mounting (2 inches / 5 cm)</p> <p>Threaded hole in front (1xM10) for clamps</p> <p>Threaded holes on the bottom (4xM5) for 50x100mm VESA plates</p> <p>Selectable fan modes for fanless, quiet, or cool operation</p> <p>Dimensions (WxDxH): 440 x 43.2 x 400 mm</p> <p>Weight: 5.45Kg (12.02lb)</p>
SOLUZIONI	
Digital Signage	Si