ClickUfficio srl
Via di San Saba, 12
00153 Roma
Telephone: 800.206.999
E-mail: info@clickufficio.it

Switch netgear av line m4250-26g4xf std0000701335	
Codice	CK211234
EAN	0606449151619
Marca	NETGEAR
Part number	GSM4230PX-100EU
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	7.925
Volume (cm³)	30806.25

24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget

2-port 10/100/1000BASE-T (RJ45)

4-port 1000/10GBASE-X (SFP+)

132 Gbps non-blocking fabric across 30 ports

Out-of-band 1G Ethernet management port

USB-C and RJ45 RS232 console ports and USB-A storage port

Front black display panel and all ports in the back

Possible reversed mounting with ports in the front

Rack-mounting standard brackets

Longer brackets for recessed mounting (2 inches / 5 cm)

Threaded hole in front (1xM10) for clamps

Threaded holes on the bottom (4xM5) for 50x100mm VESA plates

Selectable fan modes for fanless, quiet, or cool operation

Dimensions (WxDxH): 440 x 43.2 x 400 mm

Weight: 5.45Kg (12.02lb)

SPECIFICHE	
Marca	NETGEAR
Numero porte LAN	30 n

ALIMENTAZIONE	
Power Supply	AC
Alimentatore incluso	Si
Consumo energetico	614 W
Alimentazione ridondata	No
Tipologia di alimentazione ridondata	Nessuna ridondanza di alimentazione
CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	Si
Nr. porte PoE	24
Quality Of Service (QOS)	Si
Supporto Routing (Layer 3)	No
Dimensioni tabella MAC	16000
Vlan supportate	4093
Modalità Stacking	No
PoE Budget	480 W
Gestione	Layer 2+
Altre caratteristiche tecniche	24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000/10GBASE-X (SFP+) 132 Gbps non-blocking fabric across 30 ports

	Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for fanless, quiet, or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 5.45Kg (12.02lb)
Industriale	No
Attacco su barra DIN	No
Stackable	No
Standard PoE supportati	30W
Nr. slot	0
CARATTERISTICHE FISICHE	
Altezza	44 mm
Larghezza	440 mm
Peso	545 gr
Profondità	400 mm
Rack-Mountable	Si
Altre caratteristiche fisiche	24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000/10GBASE-X (SFP+) 132 Gbps non-blocking fabric across 30 ports Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for fanless, quiet, or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 5.45Kg (12.02lb)
Nr. unità rack	1
CONNETTIVITÀ	

Porta Console	Si
Nr. porte LAN	30 N
Altre informazioni sulla connettività	24-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000/10GBASE-X (SFP+) 132 Gbps non-blocking fabric across 30 ports Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for fanless, quiet, or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 5.45Kg (12.02lb)
Nr. porte Uplink	4
Tipo e velocità porte LAN	RJ-45 10/100/1000
Tipo e velocità porte Uplink	SFP/SFP+
SOLUZIONI	
Digital Signage	Si