

<p>Switch NETGEAR GSM4248PX-100EUS GSM4248PX-100EU</p>	
<p>Codice</p>	<p>CK211529</p>
<p>EAN</p>	<p>0606449151732</p>
<p>Marca</p>	<p>NETGEAR</p>
<p>Part number</p>	<p>GSM4248PX-100EU</p>
<p>Storage unit</p>	
<p>Unità di vendita</p>	<p>Cadauno</p>
<p>Confezione</p>	<p>1</p>
<p>Imballaggio</p>	<p>1</p>
<p>Peso (kg)</p>	<p>8.85</p>
<p>Volume (cm³)</p>	<p>29256</p>
<p>40-port 10/100/1000BASE-T (RJ45) PoE+ with 960W PoE budget 8-port 1000/10GBASE-X (SFP+) 240 Gbps non-blocking fabric across 48 ports Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for quiet or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 6.31Kg (13.91lb)</p>	

SPECIFICHE	
Marca	NETGEAR
Numero porte LAN	40 n

ALIMENTAZIONE	
Power Supply	AC
Alimentatore incluso	Si
Consumo energetico	1197 W
Alimentazione ridondata	No
Tipologia di alimentazione ridondata	Nessuna ridondanza di alimentazione

CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	Si
Nr. porte PoE	40
Quality Of Service (QOS)	Si
Supporto Routing (Layer 3)	Si
Dimensioni tabella MAC	16000
Vlan supportate	4093
Modalità Stacking	No
PoE Budget	960 W
Gestione	Layer 2+
Altre caratteristiche tecniche	<p>40-port 10/100/1000BASE-T (RJ45) PoE+ with 960W PoE budget</p> <p>8-port 1000/10GBASE-X (SFP+)</p> <p>240 Gbps non-blocking fabric across 48 ports</p> <p>Out-of-band 1G Ethernet management port</p> <p>USB-C and RJ45 RS232 console ports and USB-A storage port</p> <p>Front black display panel and all ports in the back</p> <p>Possible reversed mounting with ports in the front</p> <p>Rack-mounting standard brackets</p> <p>Longer brackets for recessed mounting (2 inches / 5 cm)</p> <p>Threaded hole in front (1xM10) for clamps</p> <p>Threaded holes on the bottom (4xM5) for 50x100mm VESA plates</p> <p>Selectable fan modes for quiet or cool operation</p> <p>Dimensions (WxDxH): 440 x 43.2 x 400 mm</p> <p>Weight: 6.31Kg (13.91lb)</p>
Industriale	No
Attacco su barra DIN	No

Stackable	No
Standard PoE supportati	30W
Nr. slot	0
Management ridondata	No
CARATTERISTICHE FISICHE	
Altezza	44 mm
Larghezza	440 mm
Peso	6310 gr
Profondità	400 mm
Rack-Mountable	Si
Altre caratteristiche fisiche	<p>40-port 10/100/1000BASE-T (RJ45) PoE+ with 960W PoE budget</p> <p>8-port 1000/10GBASE-X (SFP+)</p> <p>240 Gbps non-blocking fabric across 48 ports</p> <p>Out-of-band 1G Ethernet management port</p> <p>USB-C and RJ45 RS232 console ports and USB-A storage port</p> <p>Front black display panel and all ports in the back</p> <p>Possible reversed mounting with ports in the front</p> <p>Rack-mounting standard brackets</p> <p>Longer brackets for recessed mounting (2 inches / 5 cm)</p> <p>Threaded hole in front (1xM10) for clamps</p> <p>Threaded holes on the bottom (4xM5) for 50x100mm VESA plates</p> <p>Selectable fan modes for quiet or cool operation</p> <p>Dimensions (WxDxH): 440 x 43.2 x 400 mm</p> <p>Weight: 6.31Kg (13.91lb)</p>
Nr. unità rack	1
CONFEZIONE	
Altri cavi inclusi	<ul style="list-style-type: none"> · M4250-40G8XF-PoE+ (GSM4248PX) · Power cord(s) · Console USB Type-C and RJ45-DB9 cables · Rackmounting standard brackets · Longer brackets for recessed mounting · Rubber footpads for tabletop installation · Installation guide
Manuali	<ul style="list-style-type: none"> · M4250-40G8XF-PoE+ (GSM4248PX) · Power cord(s) · Console USB Type-C and RJ45-DB9 cables · Rackmounting standard brackets · Longer brackets for recessed mounting · Rubber footpads for tabletop installation · Installation guide

Software	<ul style="list-style-type: none"> · M4250-40G8XF-PoE+ (GSM4248PX) · Power cord(s) · Console USB Type-C and RJ45-DB9 cables · Rackmounting standard brackets · Longer brackets for recessed mounting · Rubber footpads for tabletop installation · Installation guide
Kit e accessori Vari	<ul style="list-style-type: none"> · M4250-40G8XF-PoE+ (GSM4248PX) · Power cord(s) · Console USB Type-C and RJ45-DB9 cables · Rackmounting standard brackets · Longer brackets for recessed mounting · Rubber footpads for tabletop installation · Installation guide
CONNETTIVITÀ	
Porta Console	Si
Nr. porte LAN	40 N
Altre informazioni sulla connettività	<p>40-port 10/100/1000BASE-T (RJ45) PoE+ with 960W PoE budget</p> <p>8-port 1000/10GBASE-X (SFP+)</p> <p>240 Gbps non-blocking fabric across 48 ports</p> <p>Out-of-band 1G Ethernet management port</p> <p>USB-C and RJ45 RS232 console ports and USB-A storage port</p> <p>Front black display panel and all ports in the back</p> <p>Possible reversed mounting with ports in the front</p> <p>Rack-mounting standard brackets</p> <p>Longer brackets for recessed mounting (2 inches / 5 cm)</p> <p>Threaded hole in front (1xM10) for clamps</p> <p>Threaded holes on the bottom (4xM5) for 50x100mm VESA plates</p> <p>Selectable fan modes for quiet or cool operation</p> <p>Dimensions (WxDxH): 440 x 43.2 x 400 mm</p> <p>Weight: 6.31Kg (13.91lb)</p>
Nr. porte Uplink	8
Tipo e velocità porte LAN	RJ-45 10/100/1000
Nr. porte fruibili contemporaneamente (LAN + Uplink)	48
Tipo e velocità porte Uplink	SFP/SFP+
SOLUZIONI	
Digital Signage	Si