


<p>Switch ALLIED TELESIS Gigabit Layer 3 Managed Switch AT-X220-52GT-50</p>	
Codice	CK242640
EAN	0767035212319
Marca	ALLIED TELESIS
Part number	AT-X220-52GT-50
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	6.27
Volume (cm ³)	37950
<p>Gigabit Layer 3 Managed Switch</p> <p>48 x 10/100/1000T copper ports and 4 x 100/1000X SFP uplinks make the x220-52GT ideal for high density connectivity at the network edge.</p> <p>KEY FEATURES</p> <p>AlliedWare Plus Enterprise-class operating system EPSR enables high-speed resilient and distributed Static and dynamic (RIP) routing for L3 environments sFlow enables network performance monitoring and optimization ACLs manage access and traffic control across the network</p>	

SPECIFICHE	
Marca	ALLIED TELESIS

Numero porte LAN	48 n
------------------	------

CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	No
Gestione	Managed (CLI)
Supporto Routing (Layer 3)	Si
Nr. porte PoE	0
Vlan supportate	4094
Industriale	Si
Stackable	Si
PoE Budget	0 W
Quality Of Service (QOS)	Si
CARATTERISTICHE FISICHE	
Rack-Mountable	Si
Larghezza	441 mm
Nr. unità rack	1
Profondità	323 mm
Altezza	44 mm
Peso	4500 gr
ALIMENTAZIONE	
Power Supply	AC
Alimentatore incluso	No
Alimentazione ridondata	No
Consumo energetico	47 W
CONNETTIVITÀ	
Nr. porte LAN	48 N
Tipo e velocità porte LAN	RJ-45 10/100/1000
Nr. porte Uplink	4
Tipo e velocità porte Uplink	N/A
Porta Console	No
Altre informazioni sulla connettività	4 x 100/1000X SFP uplinks