

Switch NETGEAR NETGEAR SMB High GSM4248P-100EUS



Codice	CK266226
EAN	0606449151640
Marca	NETGEAR
Part number	6315526
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	8.31
Volume (cm ³)	29574

40-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget
 8-port 1000BASE-X (SFP)
 96 Gbps non-blocking fabric across 48 ports
 Out-of-band 1G Ethernet management port
 USB-C and RJ45 RS232 console ports and USB-A storage port
 Front black display panel and all ports in the back
 Possible reversed mounting with ports in the front
 Rack-mounting standard brackets
 Longer brackets for recessed mounting (2 inches / 5 cm)
 Threaded hole in front (1xM10) for clamps
 Threaded holes on the bottom (4xM5) for 50x100mm VESA plates
 Selectable fan modes for fanless, quiet, or cool operation
 Dimensions (WxDxH): 440 x 43.2 x 400 mm
 Weight: 5.85Kg (12.90lb)

SPECIFICHE	
Marca	NETGEAR
Numero porte LAN	40 n

CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	Si
Gestione	Layer 2+
Supporto Routing (Layer 3)	No
Nr. porte PoE	40
Vlan supportate	4093
Industriale	No
Stackable	No
PoE Budget	480 W
Attacco su barra DIN	No
Quality Of Service (QOS)	Si
Modalità Stacking	No
Dimensioni tabella MAC	16000
Standard PoE supportati	30W
Altre caratteristiche tecniche	<p>40-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget</p> <p>8-port 1000BASE-X (SFP)</p> <p>96 Gbps non-blocking fabric across 48 ports</p> <p>Out-of-band 1G Ethernet management port</p> <p>USB-C and RJ45 RS232 console ports and USB-A storage port</p> <p>Front black display panel and all ports in the back</p> <p>Possible reversed mounting with ports in the front</p> <p>Rack-mounting standard brackets</p> <p>Longer brackets for recessed mounting (2 inches / 5 cm)</p> <p>Threaded hole in front (1xM10) for clamps</p> <p>Threaded holes on the bottom (4xM5) for 50x100mm VESA plates</p> <p>Selectable fan modes for fanless, quiet, or cool operation</p> <p>Dimensions (WxDxH): 440 x 43.2 x 400 mm</p> <p>Weight: 5.85Kg (12.90lb)</p>
Management ridondata	No
CARATTERISTICHE FISICHE	
Rack-Mountable	No

Larghezza	440 mm
Nr. unità rack	0
Profondità	400 mm
Altezza	44 mm
Peso	5900 gr
Altre caratteristiche fisiche	<p>40-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget</p> <p>8-port 1000BASE-X (SFP)</p> <p>96 Gbps non-blocking fabric across 48 ports</p> <p>Out-of-band 1G Ethernet management port</p> <p>USB-C and RJ45 RS232 console ports and USB-A storage port</p> <p>Front black display panel and all ports in the back</p> <p>Possible reversed mounting with ports in the front</p> <p>Rack-mounting standard brackets</p> <p>Longer brackets for recessed mounting (2 inches / 5 cm)</p> <p>Threaded hole in front (1xM10) for clamps</p> <p>Threaded holes on the bottom (4xM5) for 50x100mm VESA plates</p> <p>Selectable fan modes for fanless, quiet, or cool operation</p> <p>Dimensions (WxDxH): 440 x 43.2 x 400 mm</p> <p>Weight: 5.85Kg (12.90lb)</p>
ALIMENTAZIONE	
Power Supply	AC
Alimentatore incluso	Si
Alimentazione ridondata	No
Consumo energetico	625 W
CONNETTIVITÀ	
Nr. porte LAN	40 N
Tipo e velocità porte LAN	RJ-45 10/100/1000
Nr. porte Uplink	8
Tipo e velocità porte Uplink	SFP 1GbE
Porta Console	Si
Nr. porte fruibili contemporaneamente (LAN + Uplink)	48
Altre informazioni sulla connettività	<p>40-port 10/100/1000BASE-T (RJ45) PoE+ with 480W PoE budget</p> <p>8-port 1000BASE-X (SFP)</p> <p>96 Gbps non-blocking fabric across 48 ports</p> <p>Out-of-band 1G Ethernet management port</p>

	<p>USB-C and RJ45 RS232 console ports and USB-A storage port</p> <p>Front black display panel and all ports in the back</p> <p>Possible reversed mounting with ports in the front</p> <p>Rack-mounting standard brackets</p> <p>Longer brackets for recessed mounting (2 inches / 5 cm)</p> <p>Threaded hole in front (1xM10) for clamps</p> <p>Threaded holes on the bottom (4xM5) for 50x100mm VESA plates</p> <p>Selectable fan modes for fanless, quiet, or cool operation</p> <p>Dimensions (WxDxH): 440 x 43.2 x 400 mm</p> <p>Weight: 5.85Kg (12.90lb)</p>
CONFEZIONE	
Altri cavi inclusi	<ul style="list-style-type: none"> · M4250-40G8F-PoE+ (GSM4230P) · Power cord(s) · Console USB Type-C and RJ45-DB9 cables · Rackmounting standard brackets · Longer brackets for recessed mounting · Rubber footpads for tabletop installation · Installation guide
Software	Web
Manuali	Link Web
Kit e accessori Vari	Montaggio a Rack
SOLUZIONI	
Digital Signage	Si