


| | |
|---|--|
| Switch D-LINK D-Link Business DXS-1210-28S |  |
| Codice | CK274780 |
| EAN | 0790069456817 |
| Marca | D-LINK |
| Part number | 6176191 |
| Storage unit | |
| Unità di vendita | Cadauno |
| Confezione | 1 |
| Imballaggio | 1 |
| Peso (kg) | 4.55 |
| Volume (cm ³) | 17271.936 |
| <p>10 Gigabit Ethernet Smart Managed Switches DXS-1210-28 Series</p> <p>10GbE bandwidth connections 25GbE SFP28 ports1 (DXS-1210-28T only) Layer 2 management and security, with Layer 3 Lite features Industry standard full CLI, web-based GUI, console port Static Routing and MSTP D-Link Limited-Lifetime Warranty after registration</p> | |

| SPECIFICHE | |
|------------|--------|
| Marca | D-LINK |

| | |
|------------------|------|
| Numero porte LAN | 24 n |
|------------------|------|

| CARATTERISTICHE TECNICHE | |
|--|---------------------|
| Power over Ethernet (PoE) | No |
| Gestione | Smart Managed (WEB) |
| Supporto Routing (Layer 3) | Si |
| Nr. porte PoE | 0 |
| Vlan supportate | 0 |
| Industriale | No |
| Stackable | No |
| PoE Budget | 0 W |
| Quality Of Service (QOS) | Si |
| CARATTERISTICHE FISICHE | |
| Rack-Mountable | No |
| Larghezza | 441 mm |
| Nr. unità rack | 0 |
| Profondità | 209,5 mm |
| Altezza | 44 mm |
| Peso | 3270 gr |
| ALIMENTAZIONE | |
| Power Supply | AC |
| Alimentatore incluso | Si |
| Alimentazione ridondata | No |
| Consumo energetico | 85,7 W |
| CONNETTIVITÀ | |
| Nr. porte LAN | 24 N |
| Tipo e velocità porte LAN | SFP+ 10GbE |
| Nr. porte Uplink | 4 |
| Tipo e velocità porte Uplink | RJ-45 10GBASE-T |
| Porta Console | Si |
| Nr. porte fruibili contemporaneamente (LAN + Uplink) | 28 |