

Motherboard ASUS ROG CROSSHAIR X670E HERO 90MB1BC0-M0EAY0	
Codice	CK291096
EAN	4711081862420
Marca	ASUS
Part number	90MB1BC0-M0EAY0
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	3.905
Volume (cm ³)	12787.5
<p>Nuove ROG CROSSHAIR X670E HERO EXTREME</p> <p>Nuovo Socket AMD AM5 per supporto nativo dei nuovissimi processori AMD Ryzen 7000 Series Overclock dinamico su tutta la gamma X670E Elevato numero di fasi di alimentazione, potenti e di ottima qualità per garantire elevate performance e affidabilità di sistema RAM DDR5 con frequenza fino a 6.400Mhz OC PCI-Express 5.0 non solo per lo slot PCI-Express 16x (scheda grafica) ma anche per Moduli SSD M.2 Maggior supporto di linee PCI-Express e maggior numero di moduli SSD installabili Dotazione di interfacce I/O molto ricche e complete Lan 2.5Gb e per le SKU aventi Wi-Fi integrato lo standard è il 6E : 2x2 Wi-Fi 6E (802.11</p>	

a/b/g/n/ac/ax) in abbinamento a Bluetooth v5.2

SPECIFICHE

Tipo	ddr5
Dimensioni	atx
Marca	ASUS
Processore Socket	am5
Connettore video	2 x type c video + 1x hdmi

SPECIFICHE TECNICHE

Connettore Video	2 x Type C video + 1x HDMI
Alimentazione	24-pin ATX, 1 x 6 pin ATX, 2 x 8 pin ATX V
Chipset	AMD X670

CANALI/CONNETTORI

USB 2.0 - interni	3
USB 2.0 - retro	0
USB 3.0 - interni	0
USB 3.0 - retro	0
USB 3.1 - interni	0
USB 3.1 - retro	0
USB 3.2 Gen 1 - interni	0
USB 3.2 Gen 2 interni	3
USB 3.2 Gen 2 retro	8
SATA revision 2.0 (SATA 3 Gbit/s)	0
SATA revision 3.0 (SATA 6 Gbit/s)	6
PCI	0
PCI-Express 16x	2
PCI-Express 1x	1
Audio	5
Connettori Speciali	3x Typce C
SATA M.2	5
Ps/2	0
Ventole chassis	4

PROCESSORE

Socket	AM5
Famiglia processore	AMD
CPU compatibili	AMD Ryzen 7000 Series
CONTROLLER	
Raid	0/1/10
LAN	1 x Intel 2.5G LAN
VIDEO	
GPU integrata	No
Modello scheda video	Non presente
Connettori scheda video	Si
Tecnologia multi GPU	NO
AUDIO INTEGRATO	
Modello scheda audio	Realtek® ALC4082 Codec
Numero Canali	7,1
MEMORIA	
Tipo Moduli	DDR5
Espansione max	128 GB
Frequenza max	6400 MHz
Numero Slot	4
Dual Channel	Si
ECC	Si
Non ECC	Si
GENERALE	
Dotazione Hardware	X
Altre Caratteristiche	Extreme OC Kit - FlexKey button - ReTry button - Start button Extreme Engine Digi+ - 10K Black Metallic Capacitors - MicroFine Alloy Choke ASUS Q-Design - M.2 Q-Latch - PCIe Slot Q-Release - Q-Code - Q-Connector - Q-DIMM - Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]) - Q-Slot ASUS Thermal Solution - M.2 heatsink backplate - M.2 heatsink - VRM heatsink design ASUS EZ DIY - BIOS FlashBack button - Clear CMOS button - ProCool II - Pre-mounted I/O shield - SafeSlot - SafeDIMM Aura Sync - Aura RGB header(s) - Addressable Gen 2 header(s) ASUS Lighting Control - RGB header(s) Front Panel USB 3.2 Gen 2x2 with Quick Charge 4+ Support - Support: up to 60W charging* - Output: 5/9/15/20V max. 3A, PPS:3.321V max. 3A - Compatible with QC 4.0/3.0/2.0, PD3.0 and PPS * To support 60W, please install the power cable to 6-pin PCIe

	Graphics Card connector or can only support 27W ROG Exclusive Software - GameFirst VI - ROG CPU-Z - Sonic Studio III + Sonic Studio Virtual Mixer + Sonic Suite Companion - Sonic Radar III - DTS® Sound Unbound - BullGuard Internet Security (1-year full version) ASUS Exclusive Software Armoury Crate - AIDA64 Extreme (1 year full version) - Aura Creator - Aura Sync - Fan Xpert 4 with AI Cooling II - Power Saving - Polymo Lighting - Two-Way AI Noise Cancellation AI Suite 3 TPU DIGI+ Power Control PC Cleaner Turbo app MyAsus WinRAR UEFI BIOS ASUS EZ DIY - ASUS CrashFree BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode
DIMENSIONI	
Form factor	ATX
SOLUZIONI	
Gaming	Si