



| | |
|---------------------------|---------------|
| Codice | CK295704 |
| EAN | 4711103083208 |
| Marca | QNAP |
| Part number | 7924916 |
| Storage unit | |
| Unità di vendita | Cadauno |
| Confezione | 1 |
| Imballaggio | 1 |
| Peso (kg) | 9.35 |
| Volume (cm ³) | 58314.536 |

With an Intel® Core i9 Processor to support the ZFS-based QuTS hero operating system, the TVS-h874 SMB NAS ensures data integrity and supports block-level inline data deduplication and compression, near-limitless snapshots, real-time SnapSync, and SSD optimization. Whether for mission-critical file servers, virtualization servers, collaborative video editing, or efficient data backup and recovery applications, the TVS-h874X delivers an ideal NAS solution. The high-performance TVS-h874X provides PCIe Gen 4 (up to twice the transmission speed of Gen 3) expandability, M.2 NVMe SSD caching, and 2.5GbE connectivity for high-speed virtualization network environments.

| SPECIFICHE | |
|------------|-------------------------------|
| Tipo | nas senza hard disk integrato |

| | |
|-------|------|
| Marca | QNAP |
|-------|------|

CARATTERISTICHE TECNICHE

| | |
|-------------------|--|
| Bus per Hard Disk | SATA |
| Supporto RAID | Si |
| Memoria DDRAM | 64000 MB |
| Memoria Flash | 5000 MB |
| Posizionamento | Office |
| Tipo File Systems | EXT4 (internal) , EXT4, EXT3, FAT, NTFS, HFS+ (External) |
| Supporto IP | No specifica |

ALIMENTAZIONE

| | |
|--------------------------------|-----------|
| Power Supply Frequenza | N/A Hz |
| Power Supply Potenza Assorbita | 45,6 W |
| Power Supply Tensione | 100/240 V |
| Power Supply | N/A |
| Alimentatore ridondato | No |

CARATTERISTICHE FISICHE

| | |
|--------------------|--|
| Altezza massima | 188,2 mm |
| Colore Chassis | Nero |
| Led | HDD 1-8, Status, LAN, USB port, M.2 port |
| Formato Chassis | Tower |
| Larghezza massima | 264,3 mm |
| Peso | 8070 gr |
| Profondità massima | 279,6 mm |

CONFEZIONE

| | |
|----------------------|---|
| Cavi Inclusi | 10GBASE-T Ethernet cable x 1 Power Cord x 1 |
| Kit e Accessori Vari | Flat head screw (for 2.5" HDD) Flat head screw (for 3.5" HDD) M.2 SSD Heatsink x 2 Drive tray keys x 2 |
| Manuali | Quick Installation Guide (QIG) |
| Software | . |

| CONFORMITÀ | |
|----------------------------------|--------------------------|
| Dichiarazione di Conformità | CE |
| CONNETTIVITÀ | |
| Porta Console | No |
| Connettori porte LAN | RJ45 |
| Numero porte LAN | 3 |
| Velocità LAN | 100/1000/2500 MB |
| Conformità LAN | 2 lan (2.5G/1G/100M/10M) |
| Numero porte USB | 5 |
| ESTENSIONI WIRELESS | |
| Estensioni wireless | No |
| Wireless Security | No |
| STORAGE | |
| Numero Bay Totali | 8 |
| Capacità Totale Dischi Inclusi | 0 GB |
| Numero Dischi Inclusi | 0 |
| Unità di memoria | SATA |
| Supporto Enclosures | No |
| Dimensione degli slot dei dischi | 2.5"/3.5" |
| PROTOCOLLI | |
| Cifs | Si |
| SMB | Si |
| AFP | Si |
| NFS | Si |
| Http | Si |
| Https | Si |
| FTP | Si |
| Ftps | Si |
| Rsync | Si |
| Iscsi | Si |
| LIVELLI RAID | |
| RAID 0 (Striping) | Si |

| | |
|--------------------|----|
| RAID 1 (Mirroring) | Si |
| Raid 5 | Si |
| Raid 6 | Si |
| Jbod | Si |