



<p><b>Switch ALCATEL-LUCENT ENTERPRISE OS2360-P24X-IT - Fixed GigE 1RU chassis, WebSmart+ OS2360-P24X-IT</b></p>	
--	--

Codice	CK298369
EAN	
Marca	ALCATEL-LUCENT ENTERPRISE
Part number	OS2360-P24X-IT
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	5.125
Volume (cm <sup>3</sup> )	20475

**OS2360-P24X-IT**

Fixed GigE 1RU chassis, WebSmart+, 24 RJ-45 PoE 10/100/1G BaseT, 2 SFP (1/10G) uplink ports, 2 SFP(+) as 1G uplinks or 10G stacking ports. Internal AC supply (370W PoE budget), Italy power cord.



SPECIFICHE	
Marca	ALCATEL-LUCENT ENTERPRISE
Numero porte LAN	24 n

CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	Si
Gestione	Layer 2+
Supporto Routing (Layer 3)	Si
Nr. porte PoE	24
Vlan supportate	1
Industriale	No
Stackable	Si
PoE Budget	740 W
Quality Of Service (QOS)	Si
Altre caratteristiche tecniche	Fixed GigE 1RU chassis, WebSmart+, 24 RJ-45 PoE 10/100/1G BaseT, 2 SFP (1/10G) uplink ports, 2 SFP(+) as 1G uplinks or 10G stacking ports. Internal AC supply (370W PoE budget), Italy power cord.

CARATTERISTICHE FISICHE	
Rack-Mountable	Si
Larghezza	440 mm
Nr. unità rack	1
Profondità	300 mm
Altezza	50 mm

Peso	3390 gr
Altre caratteristiche fisiche	OmniSwitch 2260 10 port mounting options <b>OS2260-RM-19-L</b> Simple L-bracket for mounting a single OS2260-10/-P10 switch in a 19 rack <b>OS2260-WALL-MNT</b> Wall mounting kit for OS2260 products, contains universal mounting brackets and screws for wall mounting OS2260 switch
<b>ALIMENTAZIONE</b>	
Power Supply	AC
Alimentatore incluso	Si
Alimentazione ridondata	No
Consumo energetico	13 W
<b>CONNETTIVITÀ</b>	
Nr. porte LAN	24 N
Tipo e velocità porte LAN	RJ-45 10/100/1000
Nr. porte Uplink	1
Tipo e velocità porte Uplink	RJ45 10/100/1000, SFP 1GbE
Porta Console	No
<b>SOLUZIONI</b>	
UCC	Si