


<p>Switch ALCATEL-LUCENT ENTERPRISE OS2360-P48X-IT - Fixed GigE 1RU chassis, WebSmart+ OS2360-P48X-IT</p>	
--	--

Codice	CK298370
EAN	
Marca	ALCATEL-LUCENT ENTERPRISE
Part number	OS2360-P48X-IT
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	5.63
Volume (cm ³)	21450

OS2360-P48X-IT

Fixed GigE 1RU chassis, WebSmart+, 48 RJ-45 PoE 10/100/1G BaseT, 2 SFP (1G) uplink ports, 2 SFP+ (1/10G) uplink ports, 2 (SFP+) as 1 G uplinks or 10G stacking ports. Internal AC supply (740W PoE budget), Italy power cord.

--

SPECIFICHE	
Marca	ALCATEL-LUCENT ENTERPRISE
Numero porte LAN	48 n

CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	Si
Gestione	Layer 2+
Supporto Routing (Layer 3)	Si
Nr. porte PoE	48
Vlan supportate	1
Industriale	No
Stackable	Si
PoE Budget	740 W
Quality Of Service (QOS)	Si
Altre caratteristiche tecniche	Fixed GigE 1RU chassis, WebSmart+, 48 RJ-45 PoE 10/100/1G BaseT, 2 SFP (1G) uplink ports, 2 SFP+ (1/10G) uplink ports, 2 (SFP+) as 1 G uplinks or 10G stacking ports. Internal AC supply (740W PoE budget), Italy power cord.

CARATTERISTICHE FISICHE	
Rack-Mountable	Si
Larghezza	440 mm
Nr. unità rack	1
Profondità	300 mm
Altezza	50 mm
Peso	3390 gr
Altre caratteristiche fisiche	OmniSwitch 2260 10 port mounting options OS2260-RM-19-L Simple L-bracket for mounting a single OS2260-10/-P10 switch in a 19 rack OS2260-WALL-MNT

	Wall mounting kit for OS2260 products, contains universal mounting brackets and screws for wall mounting OS2260 switch
ALIMENTAZIONE	
Power Supply	AC
Alimentatore incluso	Si
Alimentazione ridondata	No
Consumo energetico	13 W
CONNETTIVITÀ	
Nr. porte LAN	48 N
Tipo e velocità porte LAN	RJ-45 10/100/1000
Nr. porte Uplink	1
Tipo e velocità porte Uplink	RJ45 10/100/1000, SFP 1GbE
Porta Console	No
SOLUZIONI	
UCC	Si