


<p>Switch ALLIED TELESIS AT-GS980M/52-50</p>	
Codice	CK311804
EAN	0767035212388
Marca	ALLIED TELESIS
Part number	AT-GS980M/52-50
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	6.33
Volume (cm <sup>3</sup> )	37424.5
<p>Allied Telesis AT-GS980M/52-50 Gestito Gigabit Ethernet (10/100/1000) GrigioThe Allied Telesis CentreCOM GS980M/52 managed switch features 48 x 10/100/1000T copper ports and 4 x 100/1000X SFP uplinks. A comprehensive feature-set, and built in security, make it ideal for high-density user and device connectivity at the network edge. <b>Overview</b> Allied Telesis GS980M Series switches provide an excellent access solution for today s networks, supporting Gigabit to the desktop for maximum performance. Deploying the GS980M as an AMF edge node when an AMF Master switch is available in the network, helps reduce network running costs by automating and simplifying many day-to-day administration tasks. 48 Gigabit ports and 4 SFP uplinks enable high-density and secure connectivity at the network edge, and the PoE+ model can supply up to 30 Watts to powered end-points.</p>	

SPECIFICHE	
Marca	ALLIED TELESIS

Numero porte LAN	48 n
------------------	------

## ALIMENTAZIONE

Alimentatore incluso	No
Consumo energetico	47 W
Alimentazione ridondata	No

## CARATTERISTICHE TECNICHE

Power over Ethernet (PoE)	No
Nr. porte PoE	0
Quality Of Service (QOS)	Si
Supporto Routing (Layer 3)	No
Dimensioni tabella MAC	16000
Vlan supportate	4094
Gestione	Managed (CLI)
Altre caratteristiche tecniche	Tecnologia delle fibre dei cavi elettrici: 100BASE-X
Tipologia Layer 3	NO
Stackable	No

## CARATTERISTICHE FISICHE

Altezza	44 mm
Larghezza	441 mm
Peso	4500 gr
Profondità	323 mm
Rack-Mountable	Si

## CONNETTIVITÀ

Porta Console	No
Nr. porte LAN	48 N
Altre informazioni sulla connettività	Connettore a fibra ottica: SFP
Tipo e velocità porte LAN	RJ-45 10/100/1000

## DIMENSIONI CON IMBALLO

Peso con imballo	6400 kg
Lato A	575 cm
Lato B	445 cm
Lato C	150 cm