


Switch ALLIED TELESIS AT-IE220-10GHX-80 AT-IE22010GHX80	
Codice	CK311808
EAN	0767035226392
Marca	ALLIED TELESIS
Part number	AT-IE22010GHX80
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	2.04
Volume (cm ³)	8849.25
<p>Allied Telesis IE220-10GHX Gestito L2 Gigabit Ethernet (10/100/1000) Supporto Power over Ethernet (PoE) Grigio Industrial Ethernet Layer 2+ PoE++ Switches with 10G uplinks Ruggedized switches built for enduring performance in harsh environments. Power over Ethernet (PoE++) connects and powers environmental, system control, and other key IIoT devices for a reliable and high-performing solution and 10G fiber uplinks ensure capacity for demanding edge applications. The IE220 Series enables safety, security, and smooth operation for building automation, intelligent transportation, and smart city networks.</p>	

SPECIFICHE	
Marca	ALLIED TELESIS
Numero porte LAN	8 n

ALIMENTAZIONE

Power Supply	DC
Alimentatore incluso	No
Consumo energetico	18,5 W
Alimentazione ridondata	No
CARATTERISTICHE TECNICHE	
Power over Ethernet (PoE)	Si
Nr. porte PoE	0
Quality Of Service (QOS)	Si
Supporto Routing (Layer 3)	No
Dimensioni tabella MAC	16000
Vlan supportate	4094
Gestione	Managed (CLI)
Altre caratteristiche tecniche	Algoritmi di sicurezza supportati: 802.1x RADIUS
Attacco su barra DIN	Si
Tipologia Layer 3	NO
Stackable	No
CARATTERISTICHE FISICHE	
Altezza	155 mm
Larghezza	65 mm
Profondità	137 mm
Rack-Mountable	No
CONNETTIVITÀ	
Porta Console	No
Nr. porte LAN	8 N
Altre informazioni sulla connettività	Quantità porte USB 2.0: 1
Tipo e velocità porte LAN	RJ-45 10/100/1000