


<p>Switch QNAP QSW-M2106PR-2S2T QSW-M2106PR2S2T</p>	
Codice	CK318702
EAN	4711103082805
Marca	QNAP
Part number	QSW-M2106PR2S2T
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	2.72
Volume (cm <sup>3</sup> )	12245.1
<p>The QNAP QSW-M2106PR-2S2T is a half-width rackmount L2 PoE Managed Switch with six 90-watt 2.5GbE PoE++ ports, two 90-watt 10GbE PoE++ ports and two 10GbE SFP+ fiber ports. Providing a total power budget of 310 watts, the QSW-M2106PR-2S2T enables a high-speed and high-power PoE network infrastructure for Wi-Fi 6/Wi-Fi 6E/Wi-Fi 7 Access Points and Routers. The QNAP Switch System (QSS) features a user-friendly web interface to help IT administrators efficiently control Layer 2 and PoE networks, including wireless APs, IP Cameras and Digital Signage, core Switches and Servers. The QSW-M2106PR-2S2T offers SMBs a cost-optimized and centrally managed LAN deployment solution. With a half-width design, two QSW-M2106PR-2S2T can be installed in a 1U rack space for space-saving.</p>	

SPECIFICHE	
Marca	QNAP

Numero porte LAN	10 n
------------------	------

### CARATTERISTICHE TECNICHE

Power over Ethernet (PoE)	Si
Gestione	Smart Managed (WEB)
Supporto Routing (Layer 3)	No
Nr. porte PoE	8
Vlan supportate	0
Industriale	No
Stackable	No
PoE Budget	0 W
Quality Of Service (QOS)	Si

### CARATTERISTICHE FISICHE

Rack-Mountable	Si
Larghezza	207 mm
Nr. unità rack	1
Profondità	248,8 mm
Altezza	43,3 mm
Peso	2540 gr

### ALIMENTAZIONE

Power Supply	AC
Alimentatore incluso	Si
Alimentazione ridondata	No
Consumo energetico	40 W

### CONNETTIVITÀ

Nr. porte LAN	10 N
Tipo e velocità porte LAN	RJ-45 10/100/1000/2500
Nr. porte Uplink	2
Tipo e velocità porte Uplink	2 x 10GBASE-T + 2 x 10GbE SFP+
Porta Console	Si
Nr. porte fruibili contemporaneamente (LAN + Uplink)	10
Altre informazioni sulla connettività	2x 10GbE SFP+ 2 2x 10GbE BASE-T (RJ45) 2

	6x 2.5GbE (RJ45) 6 8x Total PoE PoE++ PSEPorts 8
--	---