

Telecamera ip AXIS 02633-001


Codice	CK318988
EAN	7331021080621
Marca	AXIS
Part number	02633-001
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	2.686
Volume (cm ³)	12696

Axis P3735-PLE Cupola Telecamera di sicurezza IP Interno e esterno 1920 x 1080 Pixel

SoffittoIdeal for wide-area surveillance, this multidirectional camera delivers excellent overviews and detailed coverage. With highly efficient power consumption, it ensures sustainable surveillance with lower operating costs. Wide area surveillance with high-quality overview 24/7

AXIS P3735-PLE offers four channels with 2 MP per channel at 30 fps letting you capture both wide-angle and zoomed-in, detailed views. It includes day/night functionality and 360° IR illumination with individually controllable LEDs and a removable IR cut filter. So, you'll enjoy clear, reflection-free footage and excellent image quality even in low light or complete darkness. Plus, Forensic WDR ensures clarity when there's both dark and light areas in the scene.

Furthermore, it's possible to run metadata and AXIS Object Analytics streams on multiple channels so you can detect and classify people and vehicles, for instance entering a user-defined area. This makes it possible to count selected objects in an area of interest and trigger an alarm if a threshold is exceeded. Brilliant Design This compact camera offers various mounting options. For instance, it can be recessed mounted for discreet surveillance or mounted in ceilings for complete 360° coverage. When mounted on corners, it offers 270° coverage. Featuring a tamper-resistant casing and integrated IP66-/IP67-rated weather shield, it's protected against rain, snow, and sunlight ideal for outdoor wall mounting. In addition, all four varifocal camera heads can be

moved and rotated to provide the optimal field of view. Plus, each head can be controlled individually so you can monitor scenes in four directions. The camera's sensors can also be twisted, so two camera heads can be positioned closer together where one captures the wide view and the other zooms in on the same target. Cost-efficient and secure With four camera heads in one camera, AXIS P3735-PLE ensures fast, accurate, and cost-effective installation. That's because there's only one camera to install, one cable to draw, one IP address, and one video management software (VMS) license. Plus, it offers market-leading energy consumption compared to multiple single-sensor cameras even with IR enabled. This ensures sustainable surveillance with lower operating costs. Thanks to remote zoom and focus capabilities, it eliminates the need for hands-on fine-tuning. Furthermore, Axis Zipstream significantly lowers bandwidth and storage requirements. And Axis Edge Vault, a hardware-based cybersecurity platform, safeguards the device and protects sensitive information from unauthorized access. Deep learning analytics Built on ARTPEC-8, this high-performance camera features a deep learning processing unit (DLPU) eliminating the need for expensive servers and allowing for a faster and more scalable system. Plus, it improves processing capabilities so you can collect and analyze even more data than before on the edge. This helps ensure fast, easy, and efficient forensic search capabilities in live or recorded video. Thanks to AXIS Object Analytics, it can detect and classify people and vehicles. Furthermore, with support for ACAP version 4, you can add value to your system with tailor-made applications based on deep learning on the edge available from Axis and our partners.

SPECIFICHE

Tipo	telecamera
Marca	AXIS
Tecnologia	ip

DIMENSIONI

Altezza	43 mm
Larghezza	255 mm
Peso	2000 gr
Profondità	255 mm

FEATURES

Angolo	Angolo di visione dell'obiettivo, verticale: 55 -23 °, Angolo di visione dell'obiettivo, orizzontale: 108 -40 °, Angolo di visione dell'obiettivo, diagonale: 131 -46 °
Numero Antenne	0
Rilevazione Movimento	No

CONTENUTO CONFEZIONE

Cavi	No
Manuale italiano	Si
Supporto	Si

CONFORMITÀ

Altre certificazioni conformità	UL ECOLOGO, CE, EAC, KC, UKCA, VCCI, cUL
HARDWARE	
Power Supply Type	PoE
Protocollo Qos	Si
Temperatura di lavoro min	-30 °C
Temperatura di lavoro max	50 °C
Alimentazione	12 V
Protocollo IPv4/v6	Si
Protocollo Http	Si
Protocollo Https	Si
capacità memoria RAM	0
capacità memoria Flash	8192
CONNESSIONI	
Numero USB Port	0
Wireless Lan	No
Numero interfacce rete	1
Tipologia interfaccia di rete	Ethernet 10/100 Base-TX
Numero intefacce management	1
GENERALE	
Colore primario	Bianco
Microfono incorporato	No
Day&Night	No
Tipologia apparato	Telecamera
Tecnologia	IP
Movimento	No
Luogo utilizzo prevalente	Interno/Esterno
Resistenza all'acqua	No
Uso Notturno	No
IMMAGINE	
Sensore	CMOS "
Rapporto focale	3,2 F
Illuminazione minima	0 lux
Durata otturazione 1/	1,5 sec
Formato video digitale	MJPEG

Altre caratteristiche immagine	2 MP
Risoluzione orizzontale massima	1920 px
Risoluzione verticale massima	1080 px
Velocità di riproduzione	30 fps
Formato foto digitale	Funzione non supportata