

Telecamera ip AXIS 02510-001	
Codice	CK332239
EAN	7331021078741
Marca	AXIS
Part number	02510-001
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	1.05
Volume (cm ³)	2743.125
Axis M4317-PLVE Cupola Telecamera di sicurezza IP Interno 2160 x 2160 Pixel Soffitto/muroSharp images Featuring a stereographic lens and Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. With a 6 MP sensor, it offers excellent image quality and a complete 180° or 360° overview, around the clock regardless of the light conditions. Plus, Lightfinder ensures lifelike colors in low light. With day/night functionality and built-in IR illumination with individually controllable LEDs, it delivers clear, reflection-free footage and excellent image quality even in low light or complete darkness. Furthermore, AXIS M4317-PLVE supports digital PTZ views as well as dewarped views such as panorama, quad, corner, and corridor. Deep learning on the edge This high-performance camera includes a deep learning processing unit (DLPU) enabling improved processing and storage capabilities. Plus, you can collect and analyze even more data than before on the edge. Additionally, it delivers valuable metadata facilitating fast, easy, and efficient forensic search capabilities in live or recorded video. Thanks to AXIS Object Analytics, it s possible to detect and classify humans, vehicles, and types of vehicles all tailored to specific needs. Furthermore, with support for ACAP version 4, you can add value to your system with tailor-made applications based on deep learning on the edge. Secure and easy Built on ARTPEC-8, AXIS M4317-PLVE offers built-in cybersecurity features to help prevent unauthorized access and safeguard your system. For	

instance, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network. This discreet, compact mini dome blends seamlessly into any environment. It s delivered factory-focused for ease of installation. And, with digital roll functionality you can remotely adjust the rotation of the camera overview no need to do it manually on each camera. Furthermore, Axis Zipstream with H.264/H.265 significantly reduces bandwidth and storage requirements.

SPECIFICHE

Tipo	telecamera
Marca	AXIS
Tecnologia	ip

DIMENSIONI

Altezza	70 mm
Larghezza	149 mm
Peso	860 gr
Profondità	149 mm

FEATURES

Angolo	Angolo di visione dell'obiettivo, orizzontale: 182 °
Numero Antenne	0
Wireless Encryption	Crittografia HTTPS
Wireless Security	TLS, 256-bit AES-XTS, EAP-TLS
Rilevazione Movimento	Si

CONTENUTO CONFEZIONE

Cavi	No
Manuale italiano	Si
Supporto	Si

CONFORMITÀ

Altre certificazioni conformità	CSA, UL/cUL, BIS, UKCA, CE, KC 55035, EN 55032 Class A, EN 50121-4, EN 61000-6-1, EN 61000-6-2, EN 61547 Australia/New Zealand: RCM AS/NZS CISPR 32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A Korea: KS C 9835, KS C 9832 Class A USA: FCC Part 15 Subpart B Class A Railway: IEC 62236-4 IEC/EN/UL 62368-1 ed. 3, CAN/CSA C22.2 No. 62368-1 ed. 3, IEC/EN 62471 risk group exempt, UN ECE R118, IS 13252 IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10, IEC/EN 60529 IP66, ISO 4892-2, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9), ISO 21207 (Method B)
---------------------------------	---

HARDWARE	
Power Supply Type	PoE
Protocollo Qos	Si
Supporto IP	Filtraggio per indirizzo IP
Temperatura di lavoro min	-40 °C
Temperatura di lavoro max	50 °C
Alimentazione	48 V
Protocollo IPv4/v6	Si
Protocollo Http	Si
Protocollo Https	Si
capacità memoria RAM	0
capacità memoria Flash	8192
CONNESSIONI	
Numero USB Port	0
Wireless Lan	No
Numero interfacce rete	1
Tipologia interfaccia di rete	Ethernet 10/100 Base-TX
Numero interfacce management	1
GENERALE	
Colore primario	Bianco
Microfono incorporato	No
Day&Night	Si
Tipologia apparato	Telecamera
Tecnologia	IP
Movimento	No
Luogo utilizzo prevalente	Interno
Resistenza all'acqua	No
Uso Notturno	Si
IMMAGINE	
Sensore	CMOS "
Rapporto focale	2,2 F
Illuminazione minima	0,03 lux
Durata otturazione 1/	1 sec
Formato video digitale	Funzione non supportata

Altre caratteristiche immagine	6 MP
Risoluzione orizzontale massima	2160 px
Risoluzione verticale massima	2160 px
Velocità di riproduzione	60 fps
Formato foto digitale	Funzione non supportata