

Telecamera ip AXIS 02738-001	
Codice	CK337688
EAN	7331021082717
Marca	AXIS
Part number	02738-001
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	4.266
Volume (cm ³)	26014.5
Axis P1388-LE Scatola Telecamera di sicurezza IP Interno e esterno 3840 x 2160 Pixel Parete This robust, outdoor camera has a clear deterrent effect. It offers excellent 8 MP image quality even in challenging light conditions. Ideal for various surveillance situations, it includes an exchangeable lens and delivers clear, sharp images you can count on. Made for the great outdoors This IP66-, IP67-, IK10- and NEMA 4X-rated camera can handle temperatures from -40 °C to 60 °C (-40 °F to 140 °F). A front heater ensures the lens is free of ice and fog. Plus, with barrel distortion correction and defogging functionality, it delivers clear, sharp images. AXIS P13 Weathershield Extension A is also available for extreme protection against snow or rain, and to prevent reflections. With electronic image stabilization, this robust camera ensures stable images despite vibration. Scene profiles can be automatically optimized to suit specific scenarios. Furthermore, with PoE and redundant DC power, you get flexible installation, and your data is safeguarded in the event of a power outage. More light or less With an exchangeable lens and i-CS support, you can quickly and easily change the lens, making this camera ideal for various surveillance situations. Use our lens calculator to select a lens that meets your specific needs. This box camera offers excellent image quality in 4K. Lightfinder 2.0 and Forensic WDR ensure true colors and great detail in challenging light or near darkness. And it offers P-Iris for images with better contrast, clarity, resolution, and depth of field. Additionally, OptimizedIR enables	

surveillance in total darkness up to 50 m (164 ft). And, with shock detection and a tampering alarm, you'll be informed if there are any attempts to interfere with the camera. **Secure and powerful** AXIS P1388-LE offers Axis Edge Vault, a hardware-based cybersecurity platform that safeguards the device and protects sensitive information from unauthorized access. Built on an Axis system-on-chip, it includes a deep learning processing unit (DLPU) so you can run advanced features and powerful analytics on the edge. For instance, AXIS Object Analytics can detect and classify humans, vehicles, and types of vehicles. This DLPU also ensures improved processing and storage capabilities so you can collect and analyze even more data than before. Plus, it delivers valuable metadata facilitating fast, easy, and efficient forensic search capabilities in live or recorded video.

SPECIFICHE

Tipo	telecamera
Marca	AXIS
Tecnologia	ip

DIMENSIONI

Altezza	271 mm
Larghezza	159 mm
Peso	2460 gr
Profondità	271 mm

FEATURES

Angolo	Campo visivo orizzontale (modulo termico): 122 - 46 °
Numero Antenne	0
Rilevazione Movimento	Si

CONTENUTO CONFEZIONE

Cavi	No
Manuale italiano	Si
Supporto	Si

CONFORMITÀ

Altre certificazioni conformità	UL/cUL, UKCA, CE, KC, EAC, VCCI, RCM
---------------------------------	--------------------------------------

HARDWARE

Power Supply Type	PoE
Protocollo Qos	Si
Temperatura di lavoro min	-40 °C
Temperatura di lavoro max	60 °C
Alimentazione	10 V
Protocollo IPv4/v6	Si

Protocollo Http	Si
Protocollo Https	Si
capacità memoria RAM	2048
capacità memoria Flash	8192
CONNESSIONI	
Numero USB Port	0
Wireless Lan	No
Numero interfacce rete	1
Tipologia interfaccia di rete	Ethernet 10/100 Base-TX
Numero interfacce management	1
GENERALE	
Colore primario	Bianco
Microfono incorporato	No
Day&Night	Si
Tipologia apparato	Telecamera
Tecnologia	IP
Movimento	No
Luogo utilizzo prevalente	Interno/Esterno
Resistenza all'acqua	No
Forma	Turret
Uso Notturno	Si
IMMAGINE	
Sensore	CMOS "
Rapporto focale	1,5 F
Illuminazione minima	0,13 lux
Durata otturazione 1/	1 sec
Formato video digitale	H.264 - H.265
Risoluzione orizzontale massima	3840 px
Risoluzione verticale massima	2160 px
Velocità di riproduzione	30 fps
Formato foto digitale	Funzione non supportata