

Telecamera ip AXIS 02914-001	
Codice	CK339996
EAN	7331021086258
Marca	AXIS
Part number	02914-001
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	3.392
Volume (cm ³)	23805
Axis P5654-E Mk II 50HZ Cupola Telecamera di sicurezza IP Interno e esterno 1920 x 1080 Pixel Soffitto AXIS P5654-E Mk II PTZ Camera This cost-effective PTZ camera offers great image quality in HDTV 1080p and wide area coverage with 77° field of view. Plus, Axis Edge Vault safeguards your device and protects sensitive information from unauthorized access. Great images anytime AXIS P5654-E MK II delivers great image quality in HDTV 1080p with 21x optical zoom. It offers wide area coverage with a 77° field of view. So, you'll benefit from a sharp overview and great detail even in mixed and low light conditions. Thanks to Lightfinder 2.0 and Forensic WDR, it provides true colors and great detail in challenging light or near darkness. And electronic image stabilization (EIS) ensures stable images despite vibration. Including four scene profiles with different image settings, it's optimized to suit specific scenarios. Furthermore, focus recall gives you instant focus even in challenging light conditions. Keeping you secure Built on the ARTPEC 7 system-on-chip, this PTZ camera includes Axis Edge Vault, a hardware-based cybersecurity platform that safeguards the device and protects sensitive information from unauthorized access. For instance, signed firmware and secure boot guarantee that the firmware hasn't been altered and ensures only authorized firmware is installed. And if needed, secure boot guarantees that the camera is completely free of malware after a factory default. And there's more This versatile camera offers support for advanced analytics. Thanks to Axis Object	

Analytics it can detect and classify people and vehicles- all tailored to specific needs. Featuring shock detection, the camera will send an alarm when it has been hit. And Advanced Gatekeeper will automatically zoom in on objects detected in pre-defined areas. Axis Zipstream technology with H.264 and H.265 significantly lowers bandwidth and storage requirements without compromising image quality. Furthermore, with IP66, NEMA 4X, and IK10 ratings, this robust and resistant camera can also handle temperatures ranging from -30°C to 50°C (-22°F to 122°F).

SPECIFICHE

Tipo	telecamera
Marca	AXIS
Tecnologia	ip

DIMENSIONI

Altezza	217 mm
Larghezza	188 mm
Peso	2500 gr
Profondità	188 mm

FEATURES

Angolo	Angolo di visione dell'obiettivo, orizzontale: 77 - 3.6 °
Numero Antenne	0
Wireless Security	EAP-TLS, HTTPS, TLS
Rilevazione Movimento	Si

CONTENUTO CONFEZIONE

Cavi	No
Manuale italiano	Si
Supporto	Si

CONFORMITÀ

Altre certificazioni conformità	UL/cUL, UKCA, CE, KC, EAC, RCM, TAA
---------------------------------	-------------------------------------

HARDWARE

Power Supply Type	PoE
Protocollo Qos	Si
Temperatura di lavoro min	-30 °C
Temperatura di lavoro max	50 °C
Alimentazione	240 V
Protocollo IPv4/v6	Si
Protocollo Http	Si

Protocollo Https	Si
capacità memoria RAM	0
capacità memoria Flash	512
CONNESSIONI	
Numero USB Port	0
Wireless Lan	No
Numero interfacce rete	1
Tipologia interfaccia di rete	Ethernet 10/100 Base-TX
Numero interfacce management	1
GENERALE	
Colore primario	Bianco
Microfono incorporato	No
Day&Night	Si
Tipologia apparato	Telecamera
Tecnologia	IP
Movimento	No
Luogo utilizzo prevalente	Interno/Esterno
Resistenza all'acqua	No
Uso Notturno	No
IMMAGINE	
Sensore	CMOS "
Zoom ottico	21 x
Zoom digitale	12 x
Rapporto focale	4,5 F
Illuminazione minima	0,01 lux
Durata otturazione 1/	2 sec
Formato video digitale	H.264 - MJPEG - MPEG-4
Risoluzione orizzontale massima	1920 px
Risoluzione verticale massima	1080 px
Velocità di riproduzione	60 fps
Formato foto digitale	H.264 - MJPEG - MPEG-4