

Telecamera ip AXIS 02812-001	
Codice	CK341010
EAN	7331021084384
Marca	AXIS
Part number	02812-001
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	1.22
Volume (cm ³)	10584
Axis P3265-LVE-3 Cupola Telecamera di sicurezza IP Interno e esterno 1920 x 1080 Pixel SoffittoFrom basic entry/exit to advanced access control, AXIS P3265-LVE-3 supports different levels of security. It comes with AXIS License Plate Verifier preinstalled and offers cost-effective license plate reading 24/7. Easy and cost-effective Ideal for automated vehicle access control, AXIS P3265-LVE-3 includes a purpose-tuned Axis dome camera and a perpetual (one-time) license for AXIS License Plate Verifier analytics. This eliminates recurring licensing fees and ensures better cost control. This easy-to-install camera captures license plates and verifies them against the allow and blocklist stored in the camera to determine if a vehicle can enter a controlled area. So, you can eliminate people-hours to man gates, and free up resources for other tasks. And, because all the processing and storage takes place in the camera, there s no need for expensive servers and bandwidth requirements are reduced. Automated license plate reading day and night AXIS P3265-LVE-3 delivers sharp images for license plate reading in all environments day and night. This vandal-resistant, IK10-rated camera is safe to use even when installed at lower, more accessible heights. Featuring shock detection, it can send an alarm when it s been hit. This camera delivers 2 MP resolution and include Axis image enhancement technologies as well as OptimizedIR to ensure the ideal image settings for license plate reading 24/7. Flexible solution This flexible, all-in-one camera kit supports different levels of security -	

from basic entry/exit to advanced access control. It offers built-in support for AXIS A1210 and AXIS A1610 Network Door Controller allowing you to integrate with credential management systems and install a card reader as backup. It offers easy integration with your video management software (VMS). And, the application s open API (application programming interface) lets you add tailor-made applications for more complex requirements. **Things to consider for license plate capture**

SPECIFICHE

Tipo	telecamera
Marca	AXIS
Tecnologia	ip

DIMENSIONI

Altezza	104 mm
Larghezza	149 mm
Peso	800 gr
Profondità	149 mm

FEATURES

Angolo	Angolo di campo visivo: 100 °
Numero Antenne	0
Rilevazione Movimento	No
Distanza minima rilevamento	7 mt

CONTENUTO CONFEZIONE

Cavi	No
Manuale italiano	Si
Supporto	No

HARDWARE

Power Supply Type	PoE
Protocollo Qos	Si
Temperatura di lavoro min	-40 °C
Temperatura di lavoro max	50 °C
Alimentazione	48 V
Protocollo IPv4/v6	Si
Protocollo Http	Si
Protocollo Https	Si
capacità memoria RAM	1024

capacità memoria Flash	8192
CONNESSIONI	
Numero USB Port	0
Wireless Lan	No
Numero interfacce rete	1
Tipologia interfaccia di rete	Ethernet 10/100 Base-TX
Numero interfacce management	1
GENERALE	
Colore primario	Bianco
Microfono incorporato	No
Day&Night	Si
Tipologia apparato	Telecamera
Tecnologia	IP
Movimento	No
Luogo utilizzo prevalente	Interno/Esterno
Resistenza all'acqua	No
Uso Notturno	Si
IMMAGINE	
Sensore	CMOS "
Rapporto focale	1,8 F
Illuminazione minima	0,1 lux
Durata otturazione 1/	1 sec
Formato video digitale	H.264
Risoluzione orizzontale massima	1920 px
Risoluzione verticale massima	1080 px
Velocità di riproduzione	60 fps
Formato foto digitale	Funzione non supportata