


55uh5q-e	
Codice	CK426232
EAN	8806096522172
Marca	LG ELECTRONICS
Part number	55UH5Q-E.AEU
Storage unit	N
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	17.4
Volume (cm ³)	162000
<p>LG 55UH5Q Pannello piatto per segnaletica digitale 139,7 cm (55") LCD Wi-Fi 500 cd/m² 4K Ultra HD Nero WebOS 24/7Superb Picture Quality with Ultra HD Resolution With the resolution of LG UHD Signage, it makes the color and details of the contents vivid and realistic. In addition, the wide viewing angle provides clear contents. Even & Slim Bezel Design The UH5Q series features perfectly balanced horizontal and vertical slim bezels, creating a visually harmonious display solution. Its specialized design simplifies installation in retail environments while delivering a truly immersive viewing experience. Convenient webOS Platform The UH5Q is equipped with a high-performance SoC that allows for multiple tasks to be performed without a separate media player. The webOS platform provides app development tools with an intuitive UI that enhances user convenience, and includes webOS partner apps to create an SI-friendly environment. Design for Space Utilization Designed with thin bezels and simple cable management, the UH5Q saves space. With specialized hidden power inlets, it can be installed close to the wall, leaving only about 13.5 mm of space with the slim bracket. Durability that Provides Reliability for LG UHD Signage Optimized for business environments Optimized for business environments, the UH5Q is protected against salt, dust, iron powder and humidity thanks to conformal partial coating on power board, allowing for stable operation. Also, its customer-centric features, such as IP5x and Shock Monitoring*, provide both reliability and</p>	

satisfaction, ensuring the durability of LG UHD signage. **Comprehensive Security** webOS Signage goes beyond security measures at the operating system (OS) level. LG Shield employs a five-tiered defense system, encompassing server, application, operating system, system, and hardware. Each layer operates independently, providing comprehensive protection against various threats. Also, the webOS platform supports ETSI EN 303 645. **SuperSign Solutions** LG SuperSign is an integrated and intuitive content management solution for creative and organized digital signage content in your space, connecting customers to a range of services with convenient user experiences. There are a variety of versions such as SuperSign Cloud, so discover and enjoy the version that best fits you.

SPECIFICHE	
Tipo	monitor
Marca	LG ELECTRONICS
Dimensione Schermo	55"

DIMENSIONI	
Altezza	711,9 cm
Larghezza	1240,1 cm
Peso	14300 Kg
Profondità	29,7 cm
SCHERMO	
Angolo di visione orizzontale	178 °
Angolo di visione verticale	178 °
Dot pitch	0 mm
Rapporto d'aspetto	16:9
Frequenza Massima	60 Hz
Frequenza Ottimale	60 Hz
Luminosità	500 cd/m ²
Lunghezza diagonale (polliciaggio)	55 "
Contrasto standard	1200 :1
Risoluzione massima verticale	2160 px
Risoluzione massima orizzontale	3840 px
Tecnologia pannello	ADS
Tempo di risposta	8 ms
Contrasto dinamico	1000000 :1
Tempo operativo	24/7
Touch Screen	No

Risoluzione video	4K (UHD)
GENERALE	
Altre Caratteristiche	webOS
Colore principale	Nero
Contenuto della confezione	Cavi inclusi: Phone
Wi-Fi	Si
Webcam Integrata	No
Alimentatore	N.D.
System on Chip (SOC)	Si
Posizionamento	Indoor
Orientazione	Orizzontale/Verticale
Classe efficienza energetica	A
CONNESSIONI	
Nr. porte DVI	0
Nr. porte HDMI	3 nr
Nr. porte VGA	0
Nr. porte DisplayPort	1
Nr. porte Ethernet	1
Nr. porte USB	2
Tipi connessione	Wi-Fi
CONSUMI	
Durata esercizio media	24 h
Potenza assorbita in esercizio	130 W
Potenza assorbita	130 W
AUDIO	
Nr. altoparlanti	2 nr.
Potenza	20 W
Multimediale	Si
REQUISITI AMBIENTALI	
Temperatura di esercizio min-max	0 °C
Temperatura min-max	40 °C
DIMENSIONI CON IMBALLO	
Peso con imballo	18100 kg
Lato A	1360 cm

Lato B	152 cm
Lato C	810 cm
VESA FLAT DISPLAY MOUNTING INTERFACE (FDMI)	
Supporto montaggio VESA	Si
Formato VESA FDMI (Flat Display Mounting Interface)	MIS-F (300x300mm)