



SI7504



Codice	CK427041
EAN	4718755095672
Marca	BENQ
Part number	9H.S3NTB.DE2
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	72.91
Volume (cm³)	831711.82843

BenQ SL7504 Pannello piatto per segnaletica digitale 190,5 cm (75") 500 cd/m² 4K Ultra HD Nero Processore integrato Android 24/7Pantone® Validated SignageA differentlevel of colorSimplify signage with the SL04 series. Accurately deliver Pantone colors, harness the power of Google, and enjoy easy content control for impactful corporate and workplace communication. A series of firsts The SL04 is the world s first signage to be Pantone® Validated, Pantone® SkinTone Validated, and Google EDLA certified, and features a vivid color gamut and powerful signage content management. Vibrant color accuracy With a 99% sRGB color gamut (CIE 1976) and innovative color modes for various scenarios, the SL04 series offers outstanding color accuracy. See the world in Pantone colors The SL04 is the world s first Pantone Validated and Pantone SkinTone Validated signage. Pantone mode delivers the vibrant hues of the Pantone palette and the nuanced tones of the Pantone SkinTone Guide to enhance color-focused workflows. Enhanced inclusivity for brand visuals Pantone SkinTone Guide colors help teams create content that authentically represents diverse skin tones, ideal for branding, marketing, and customer communications. Your MacBook®, faithfully displayedM-book mode ensures that the colors you see on your MacBook are accurately displayed on the SL04. Details made clearer than everHigh-detail mode enhances schematics, blueprints, and floor plans with improved contrast for

greater clarity and precision in professional workflows involving architecture, engineering, urban planning, interior design, and more. Your sketches brought to lifeSketch mode mimics the look of paper by converting images to grayscale, adding a subtle warmth, and reducing display brightness. This enhances visual comfort and saves energy, making it ideal for creative teams in design, product development, fashion, and more. A truly cinematic experience Cinema mode lets you play video projects, films, and signage videos with vivid colors and depth. Connect an HDMI cable for HDR10 delivery and enjoy brighter highlights, deeper blacks, and richly detailed shadows for an immersive visual experience. Your signage solution is hereVibrant brightness across your workplaceWith 500 nits of brightness, the SL04 can easily display your content in lobbies, meeting rooms, break areas, and more. Easy on the eves Enjoy reduced eye strain with an improved anti-glare screen and low blue light technology. Connect for a complete experienceMaximize the Google ecosystem on the SL04 by connecting USB devices such as a keyboard and mouse for truly seamless collaboration. Display your wayMount the VESAcompatible SL04 in portrait or landscape mode to fit a variety of digital signage applications. Audiovisual excellence The SL04 s powerful twin 12W speakers and stunning 4K display deliver captivating audiovisual experiences, bringing your content to life. Control is in your handsProtect your display with the SL04 s IR sensor lock, preventing unauthorized access from universal remotes. Enhanced hardware security Dedicated Wi-Fi and USB covers add a further layer of protection at the hardware level for all your SL04 signage. Effortless remote signage With X-Sign, you can easily manage content from any location. Update content on SL04 displays in real time, schedule playlists in advance, and keep your message consistent across all your spaces. Manage messages from anywhere Whether it s a welcome message, an event highlight, or a daily update, X-Sign makes it easy to design and display content across every SL04 screen in your organization. No surprise pop-upsWith X-Sign, you don't need to worry about your content being interrupted by message windows and other system alerts, making for a seamless signage solution. Streamlined management The BenQ ecosystem makes managing devices, apps, and user accounts simpler than ever to reduce the workload of IT and admin staff. Giving IT control from anywhere The BenQ Device Management Solution (DMS) lets IT admins manage SL04 signage remotely, handling device settings, power schedules, firmware updates, app installations, and more. Easy provisioning Easily provision multiple new SL04 displays by scanning the barcode on the box or device to connect them to DMS. Timely firmware updates Schedule automatic firmware updates to ensure your SL04 displays always have the latest features and security patches. Designed for next-level collaboration Easily share any content in meetings Effortlessly share content across devices with InstaShare 2. Compatible with Windows, Android, macOS, iOS, iPadOS, and ChromeOS. InstaShare 2 allows wireless casting and includes a built-in smart controller for seamless presentation control. Your files, your spaceSecurely log into your BenQ account with the scan of a QR code to find your cloud drives, pinned apps, and website bookmarks. Plus, only you can see your data on the SL04.ENERGY STAR® certifiedThe SL04 series is ENERGY STAR 8.0 certified, making it easier for you to lower emissions and cut down on energy costs. Reduced packaging We ve decreased the display s packaging size by half, improving transport efficiency by 60% and cutting emissions. Easy energy control Easily set sleep modes, remote power scheduling, and get real-time energy usage insights with DMS.

SPECIFICHE	
Tipo	monitor
Marca	BENQ
Dimensione Schermo	75"

DIMENSIONI	
Altezza	959 cm

Larghezza	1679,7 cm
Peso	29000 Kg
Profondità	56,8 cm
SCHERMO	
Dot pitch	0 mm
Rapporto d'aspetto	16:9
Frequenza Massima	60 Hz
Frequenza Ottimale	60 Hz
Luminosità	500 cd/m <sup>2</sup>
Lunghezza diagonale (polliciaggio)	75 "
Contrasto standard	1200 :1
Risoluzione massima verticale	2160 px
Risoluzione massima orizzontale	3840 px
Tecnologia pannello	IPS
Tempo di risposta	8 ms
Tempo operativo	24/7
Touch Screen	No
Risoluzione video	4K (UHD)
Risoluzione video  GENERALE	4K (UHD)
	4K (UHD) Android
GENERALE	
GENERALE Altre Caratteristiche	Android
GENERALE  Altre Caratteristiche  Colore principale	Android Nero
GENERALE  Altre Caratteristiche  Colore principale  Contenuto della confezione	Android Nero Cavi inclusi: HDMI
GENERALE  Altre Caratteristiche  Colore principale  Contenuto della confezione  Webcam Integrata	Android Nero Cavi inclusi: HDMI No
GENERALE  Altre Caratteristiche  Colore principale  Contenuto della confezione  Webcam Integrata  Alimentatore	Android Nero Cavi inclusi: HDMI No N.D.
GENERALE  Altre Caratteristiche  Colore principale  Contenuto della confezione  Webcam Integrata  Alimentatore  Posizionamento	Android Nero Cavi inclusi: HDMI No N.D. Indoor
Altre Caratteristiche Colore principale Contenuto della confezione Webcam Integrata Alimentatore Posizionamento Orientazione	Android Nero Cavi inclusi: HDMI No N.D. Indoor
Altre Caratteristiche Colore principale Contenuto della confezione Webcam Integrata Alimentatore Posizionamento Orientazione CONNESSIONI	Android Nero Cavi inclusi: HDMI No N.D. Indoor Orizzontale/Verticale
Altre Caratteristiche Colore principale Contenuto della confezione Webcam Integrata Alimentatore Posizionamento Orientazione CONNESSIONI Nr. porte DVI	Android Nero Cavi inclusi: HDMI No N.D. Indoor Orizzontale/Verticale
Altre Caratteristiche Colore principale Contenuto della confezione Webcam Integrata Alimentatore Posizionamento Orientazione CONNESSIONI Nr. porte DVI Nr. porte HDMI	Android Nero Cavi inclusi: HDMI No N.D. Indoor Orizzontale/Verticale
GENERALE  Altre Caratteristiche  Colore principale  Contenuto della confezione  Webcam Integrata  Alimentatore  Posizionamento  Orientazione  CONNESSIONI  Nr. porte DVI  Nr. porte HDMI  Nr. porte VGA	Android Nero Cavi inclusi: HDMI No N.D. Indoor Orizzontale/Verticale
Altre Caratteristiche Colore principale Contenuto della confezione Webcam Integrata Alimentatore Posizionamento Orientazione CONNESSIONI Nr. porte DVI Nr. porte HDMI Nr. porte VGA Nr. porte DisplayPort	Android Nero Cavi inclusi: HDMI No N.D. Indoor Orizzontale/Verticale  0 2 nr 0 0

CONSUMI		
Durata esercizio media	24 h	
Potenza assorbita in esercizio	120,8 W	
Potenza assorbita	120,8 W	
AUDIO		
Nr. altoparlanti	2 nr.	
Potenza	24 W	
Multimediale	Si	
REQUISITI AMBIENTALI		
Temperatura di esercizio min-max	0 °C	
Temperatura min-max	40 °C	
DIMENSIONI CON IMBALLO		
Lato A	1883 cm	
Lato B	186 cm	
Lato C	1140 cm	
VESA FLAT DISPLAY MOUNTING INTERFACE (FDMI)		
Supporto montaggio VESA	Si	
Formato VESA FDMI (Flat Display Mounting Interface)	MIS-F (600x400mm)	