

55ul3q-e	
Codice	CK428575
EAN	8806096497487
Marca	LG ELECTRONICS
Part number	55UL3Q-E.AEUQ
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	15.5
Volume (cm ³)	134808
LG 55UL3Q-E visualizzatore di messaggi Pannello piatto per segnaletica digitale 139,7 cm (55") LED Wi-Fi 350 cd/m² 4K Ultra HD Nero 16/7 Superb Picture Quality with Ultra HD Resolution With the resolution of UHD, it makes the color and details of the contents vivid and realistic. In addition, the wide viewing angle provides clear contents. High-Performance with LG webOS 6.1 LG webOS 6.1 is available on the UL3Q series for smooth execution of multiple tasks. The LG webOS smart signage platform enhances user convenience with an intuitive GUI*. Easy Installation with Uniform Bezel Design The UL3Q series features perfectly balanced horizontal and vertical bezels, creating a visually harmonious display solution. Its specialized design simplifies installation in retail environments while delivering a truly immersive viewing experience. The sophisticated, symmetrical bezels enhance the aesthetic appeal of any space, transforming ordinary displays into elegant focal points. Adaptive Viewing Experience Experience enhanced flexibility with the UL3Q's innovative Face Up/Down tilt support. Whether mounted high or low, each display can adjusted to better meet viewers at eye level, promoting maximum engagement regardless of installation height. This versatility optimizes both spatial efficiency and visual comfort, delivering clear information from various viewing angles. Remote Monitoring and Control This web-based monitoring solution is user-friendly and allows the user to be at ease. It enables the user to have full access anywhere at anytime from their mobile phone & PC under network-	

accessible environment while having access to both current and past data. It allows the user to monitor the unit, make adjustments and control the unit remotely in real time. **Built-In Brightness Sensor** The UL3Q's front-mounted sensor automatically adjusts brightness to match various lighting conditions, helping to optimize viewing quality and energy efficiency without manual intervention. This adaptive feature helps maintain consistent display performance while supporting power savings, delivering improved visual experience that responds to environmental changes. **Advanced Security Architecture** The UL3Q incorporates LG's Enhanced Kernel Protection (EKP) technology, safeguarding critical data from unauthorized access and potential security threats. This commitment to information security is validated by the ISO/IEC 15408 Common Criteria EAL2 certification, providing businesses with the confidence that their sensitive content and operations remain protected in today's challenging security landscape. **Award-Winning Sustainability** The UL3Q series embodies LG Display's ESG commitment: "Better Life for All." This company-wide dedication to environmental responsibility has earned the prestigious 2025 EcoVadis Platinum medal, placing us among the top 1% of global companies for sustainability excellence. **LG ConnectedCare** Maintenance is easy and fast with the optional LG ConnectedCare* service, a cloud service solution provided by LG. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, supporting the stable operation of clients' businesses.

SPECIFICHE	
Tipo	monitor
Marca	LG ELECTRONICS
Dimensione Schermo	55"

DIMENSIONI	
Altezza	706,7 cm
Larghezza	1234,2 cm
Peso	12 Kg
Profondità	58,9 cm
SCHERMO	
Angolo di visione orizzontale	178 °
Angolo di visione verticale	178 °
Dot pitch	0 mm
Rapporto d'aspetto	16:9
Frequenza Massima	60 Hz
Frequenza Ottimale	60 Hz
Luminosità	350 cd/m²
Lunghezza diagonale (pollici)	55 "
Contrasto standard	1200 :1
Risoluzione massima verticale	2160 px
Risoluzione massima orizzontale	3840 px

Tecnologia pannello	LED
Tempo di risposta	8 ms
Contrasto dinamico	1000000 :1
Tempo operativo	16/7
Touch Screen	No
Risoluzione video	4K (UHD)
GENERALE	
Colore principale	Nero
Contenuto della confezione	Cavi inclusi: Power
Wi-Fi	Si
Webcam Integrata	No
Alimentatore	N.D.
Posizionamento	Indoor
Orientazione	Orizzontale/Verticale
Classe efficienza energetica	B
CONNESSIONI	
Nr. porte DVI	0
Nr. porte HDMI	3 nr
Nr. porte VGA	0
Nr. porte Ethernet	1
Tipi connessione	Wi-Fi
CONSUMI	
Durata esercizio media	16 h
Potenza assorbita in esercizio	98 W
Potenza assorbita	98 W
AUDIO	
Nr. altoparlanti	2 nr.
Potenza	20 W
Multimediale	Si
REQUISITI AMBIENTALI	
Temperatura di esercizio min-max	0 °C
Temperatura min-max	40 °C
DIMENSIONI CON IMBALLO	
Peso con imballo	15400 kg

Lato A	1380 cm
Lato B	825 cm
Lato C	118 cm
VESA FLAT DISPLAY MOUNTING INTERFACE (FDMI)	
Supporto montaggio VESA	Si
Formato VESA FDMI (Flat Display Mounting Interface)	MIS-F (300x300mm)