


50ul5q-e	
Codice	CK432496
EAN	8806096602140
Marca	LG ELECTRONICS
Part number	50UL5Q-E-AEUQ
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	12.2
Volume (cm ³)	109250
<p>LG 50UL5Q-E visualizzatore di messaggi Pannello piatto per segnaletica digitale 127 cm (50") LED Wi-Fi 350 cd/m² 4K Ultra HD Nero WebOS 24/7 Superb Picture Quality with Ultra HD Resolution The UL5Q-E series, with UHD resolution, enhances the realism of colors and details in the content. Its wide viewing angle offers clear visuals, while its 500-nit brightness vividly showcases the content. High-Performance with LG webOS 6.1 LG webOS 6.1 is available on the UL5Q-E series for smooth execution of multiple tasks. The LG webOS smart signage platform enhances user convenience with an intuitive GUI. Even Bezel Design The UL5Q-E series features even bezels, enhancing the aesthetic appeal of various spaces. These uniform bezels not only facilitate easy installation but also transform standard displays into elegant focal points. Adaptive Viewing Experience Experience the flexibility with the UL5Q-E series' up/down tilt capability. Whether mounted high or low, the display can be adjusted to eye level, offering viewer engagement regardless of installation height. This versatility not only enhances spatial efficiency but also provides visual comfort, delivering clear information from various viewing angles. Engineered for 24/7 Operation Built for environments that never sleep, the UL5Q-E series features panel technology that enables 24/7 operation. Built-In Brightness Sensor The UL5Q-E series' front-mounted brightness sensor automatically adjusts brightness to match various lighting conditions, optimizing viewing quality and energy efficiency without manual intervention. This</p>	

adaptive feature offers consistent display performance while also supporting power optimization, delivering a visual experience that dynamically responds to environmental changes. **Advanced Security Architecture** The UL5Q-E series incorporates LG's Enhanced Kernel Protection (EKP) technology, safeguarding critical data from unauthorized access and potential security threats. This commitment to information security is validated by the ISO/IEC 15408 Common Criteria EAL2 certification, providing businesses with the confidence that their sensitive content and operations remain protected in today's challenging security landscape. **Remote Monitoring and Control** This web-based monitoring solution is user-friendly and allows the user to be at ease. It enables the user to have full access anytime, anywhere from their mobile phone & PC in a network-accessible environment, with access to both current and past data. It allows the user to monitor the unit, make adjustments, and control the unit remotely in real time. **EPEAT Registered** The Electronic Product Environmental Assessment Tool (EPEAT) is a method for several layers of customers to evaluate the effect of a product on the environment. UL5Q-E series is an EPEAT Bronze-certified* display which means that it meets all the required criteria in the Computers and Displays category. **LG ConnectedCare** Maintenance is easy and fast with the optional LG ConnectedCare* service, a cloud service solution provided by LG. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, supporting the stable operation of clients' businesses.

SPECIFICHE	
Tipo	monitor
Marca	LG ELECTRONICS
Dimensione Schermo	50"

DIMENSIONI	
Altezza	64,14 cm
Larghezza	112,02 cm
Peso	9300 Kg
Profondità	5,99 cm
SCHERMO	
Angolo di visione orizzontale	178 °
Angolo di visione verticale	178 °
Dot pitch	0 mm
Rapporto d'aspetto	16:9
Frequenza Massima	60 Hz
Frequenza Ottimale	60 Hz
Luminosità	500 cd/m ²
Lunghezza diagonale (pollici)	50 "
Contrasto standard	1200 :1
Risoluzione massima verticale	2160 px
Risoluzione massima orizzontale	3840 px

Tecnologia pannello	LED
Tempo di risposta	8 ms
Contrasto dinamico	1000000 :1
Tempo operativo	24/7
Touch Screen	No
Risoluzione video	4K (UHD)
GENERALE	
Altre Caratteristiche	webOS
Colore principale	Nero
Contenuto della confezione	Cavi inclusi: Power
Wi-Fi	Si
Webcam Integrata	No
Alimentatore	N.D.
Posizionamento	Indoor
Orientazione	Orizzontale/Verticale
Classe efficienza energetica	G
CONNESSIONI	
Nr. porte DVI	0
Nr. porte HDMI	3 nr
Nr. porte VGA	0
Nr. porte Ethernet	1
Tipi connessione	Wi-Fi
CONSUMI	
Durata esercizio media	24 h
Potenza assorbita in esercizio	115 W
Potenza assorbita	115 W
AUDIO	
Nr. altoparlanti	2 nr.
Potenza	20 W
Multimediale	Si
REQUISITI AMBIENTALI	
Temperatura di esercizio min-max	0 °C
Temperatura min-max	40 °C
DIMENSIONI CON IMBALLO	

Peso con imballo	12,2 kg
Lato A	112,5 cm
Lato B	76 cm
Lato C	11,8 cm
VESA FLAT DISPLAY MOUNTING INTERFACE (FDMI)	
Supporto montaggio VESA	Si
Formato VESA FDMI (Flat Display Mounting Interface)	MIS-E (200x200mm)