

Videoproiettore hd 1080 (1920x1080) 5.000 ansi lumen BENQ 9H.JTJ77.16E	
Codice	CK433025
EAN	4718755096686
Marca	BENQ
Part number	9H.JTJ77.16E
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	8.756
Volume (cm ³)	65395
<p>BenQ LH860ST Proiettore a corto raggio 5000 ANSI lumen DLP 1080p (1920x1080) Compatibilità 3D NeroImmersive Entertainment Ready for demanding interactive projection projects BenQ Immersive Entertainment Projector Series Installer Ready Simulation-grade visual system, factory-tuned for accuracy *Preset configuration. Automatic edge blending software not included. Additional software or hardware is required to complete edge blending. Blending Ready Mode One-click preset in the OSD that applies key settings to prepare images for multi-projector blending. * Preset configuration. Automatic edge blending software not included. Additional software or hardware is required to complete edge blending. Brilliant visuals with accurate colour and stable performance The LH860ST delivers brilliant image clarity and stable performance across every detail from vivid Rec.709 colour and high contrast to 5000-lumen brightness and 20,000-hour laser life. BenQ WBA for Seamless Multi-Projector White Calibration BenQ s factory white balance adjustment (WBA) reduce variables between images projected from different projectors, significantly reducing manual calibration effort. It can save up to a full day of setup time in large-scale installations while ensuring seamless multi-projector alignment for edge blending. Full Flexibility for Ceilings, Walls and Floors Design for Compact Setups and Ceilings Dust Protection and Easy Maintenance 1. IP6X Sealed Engine Design Shields the projector s optical engine from dust intrusion, ensuring long-term stability and reliable performance. 2.</p>	

Optional Air Filter for Extra Protection Provides added protection in dusty environments and helps extend projector life. 3. Auto Reset Mechanism Automatically tracks filter usage and resets the timer when a new filter is installed, without any manual setup. **IT Takes Control Streamlined Device Management Remote Monitoring and Diagnostics** Easily track projector status and diagnose issues remotely, eliminating frequent on-site visits. **Firmware Management Over Network** Easily update all projectors via LAN to keep firmware current without physical access. **Reliable Performance, Less Maintenance** Ensure long-term stability, freeing SI teams to focus on creative installations rather than routine upkeep.

SPECIFICHE

Risoluzione	hd 1080 (1920x1080)
Luminosità	5.000 ansi lumen
Marca	BENQ
Contrasto	3.000.000 :1

INCLUSO NELLA CONFEZIONE

Borsa	No
Telecomando	Si
Altro	Telecomando portatile, Batterie incluse, Occhiali 3D inclusi, Staffe di montaggio incluse
Foro per cavo di sicurezza	No

AUDIO

Altoparlanti	1
Modalità uscita	Mono
Potenza uscita	10 W

CONNESSIONI GENERALI

Bluetooth	No
Seriale (RS232)	Si
USB standard	2
Rete Lan	Si
Mini USB	1
Memory Card	No
Conessioni Opzionali	Porta di sincronizzazione 3D
Wireless	Si
USB Potenza	8

CONNESSIONI INGRESSI

Ingresso Component	0 nr
--------------------	------

Ingresso DVI	0
Ingresso HDMI	2
Ingresso Video Composito	0
Ingresso Audio RCA	0
Ingresso S-Video	0
Ingresso VGA (D-SUB)	0
Ingresso Audio Jack 3,5 mm	0
Display Port	Si
Ingresso MHL	0
IMMAGINE	
Dimensioni Immagine massima	0 mt
Risoluzione massima	HD 1080 (1920x1080)
Distanza proiezione max	3,33 mt
Distanza proiezione min	0,33 m
Luminosità	5000 ANSI lumen
Rapporto contrasto	3000000 :1
Formato	16:9
Risoluzione Nativa	HD 1080 (1920x1080)
Dimensione immagine minima	0 mt
GENERALE	
Silenziosità in esercizio	36 dB
Tipologia	Home Cinema
Colore primario	Nero
Tecnologia	DLP
Silenziosità in stand-by	31 dB
Lente incorporata	No
Interattivo	No
Focale	Corta
ZOOM	
Fattore	1 x
Messa a Fuoco	Manuale
Correzione della distorsione trapezoidale verticale Min	-30
Correzione della distorsione	30

trapezoidale verticale Max	
Correzione della distorsione trapezoidale orizzontale Min	-30
Correzione della distorsione trapezoidale orizzontale Max	30
Direzione correzione distorsione trapezoidale	Orizzontale e Verticale
Altre Caratteristiche	Tipo di zoom: Fisso
Correzione Trapezoidale	Digitale
Throw Ratio Minimo	0,5 :1
Throw Ratio Massimo	0,5 :1
CONNESSIONI USCITE	
Uscita Audio Analogica	1
Uscita Audio Digitale	0
Uscita VGA	1
Uscita HDMI	0
12V Trigger	Si
SORGENTE DI LUCE	
Durata Sorgente	20000 h
Durata Sorgente mod. Economica	30000
Potenza Sorgente	281 W
Tipo di Sorgente	Laser Fosfori
CONSUMI E REQUISITI AMBIENTALI	
Temperatura min esercizio	0 °
Temperatura max esercizio	40
Potenza Massimo di Esercizio	281 W
Tensione Richiesta	100-240v, 50-60Hz
DIMENSIONI E PESO	
Altezza	13,06 cm
Larghezza	34,38 cm
Peso	5,2 kg
Profondità	26,55 cm
SOLUZIONI	
Scuola Digitale	Generico