

Switch ZYXEL XMG223052HPZZ11	
Codice	CK469872
EAN	4718937645336
Marca	ZYXEL
Part number	XMG223052HPZZ11
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	7.35
Volume (cm ³)	28305.25
Zyxel XMG2230-52HP Gestito L2/L3 2.5G Ethernet (100/1000/2500) Supporto Power over Ethernet (PoE) 1U NeroFlexible Multi-Gig port configuration for diversified deployments The XMG2230-28HP offers PoE-capable 2.5G Multi-Gig ports, while the XMG2230-52HP provides a mix of 1G and 2.5G PoE ports. Both models include four 10G SFP+ fiber uplinks for high-speed connectivity. The 52-port model s port mix enables efficient bandwidth allocation based on device needs, balancing cost and performance for scalable, future-proof networks. Dual power for always-on connectivity The XMG2230 Series is designed with superior network resiliency in mind, featuring dual power sources: an internal AC input as the primary source and an optional DC input for connection to an external DC power system. This active-standby power redundancy enables automatic switchover to backup power if the main AC source fails. The dual power design helps prevent unexpected outages and ensures stable, 24/7 connectivity. High-power, adaptive PoE for modern business devices The XMG2230-28HP supports PoE++ on all ports, while the XMG2230-52HP offers a mix of PoE+ and PoE++ for greater deployment flexibility. The series provides adaptive PoE power budget with either internal AC power 700W (28HP)/960W (52HP) or external DC power system 1440W (28HP)/2400W (52HP). It is built for higher capacity, improved efficiency, and reliable operation in demanding environments such as high-performance WiFi, video conferencing, IP surveillance, thin/zero clients, smart building, IoT, and	

AV applications. **Segment your network more effectively for security** Designed for SME networks, this series of switches supports full L2 feature sets such as VLAN, ACL, port aggregation, and mirroring, along with advanced security to keep your business protected. It also provides essential L3 access features for converged voice, video, and data. With support for static routing, the switches ensure efficient traffic flows across your network, while the built-in DHCP server simplifies device onboarding and reduces IT overhead. **Click. Tap. Done.** Get up and running in minutes with the Nebula mobile app. With just a few simple clicks, our user-friendly step-by-step wizard walks you through the entire installation process, no technical expertise required. Once connected, the intuitive interface gives you complete control, making it easy to adjust settings, monitor performance and manage your network anytime, anywhere. Search: Zyxel Nebula Mobile **Powerful, effortless and scalable connectivity.** With Nebula, you can manage your entire network wireless, switching, security and LTE/5G through a single centralized cloud platform. Deploy and configure devices quickly and remotely, without the need for extra hardware controllers or software. Whether you're managing one site or many, Nebula delivers real-time monitoring, instant alerts and complete network visibility anytime, anywhere. Scale confidently, simplify operations and stay secure all through one intuitive platform. **Dedicated networked AV mode** The Networked AV mode in standalone mode simplifies deployment with an intuitive setup wizard and AI-driven auto-configuration. A visual dashboard highlights key AV settings like IGMP, while a simplified menu streamlines management. With high performance plus built-in Dante and AES67 profile support, the XMG2230 ensures smooth, reliable AVoIP streaming for professional AV environments.

SPECIFICHE

Marca	ZYXEL
Numero porte LAN	48 n

ALIMENTAZIONE

Power Supply	AC
Alimentatore incluso	Si
Consumo energetico	2525 W
Alimentazione ridondata	No

CARATTERISTICHE TECNICHE

Power over Ethernet (PoE)	Si
Nr. porte PoE	0
Quality Of Service (QOS)	Si
Supporto Routing (Layer 3)	Si
Dimensioni tabella MAC	32000
Vlan supportate	4094
PoE Budget	2400 W
Gestione	Managed (CLI)
Industriale	No
Stackable	Si

Nr. slot	16
CARATTERISTICHE FISICHE	
Altezza	44 mm
Larghezza	441 mm
Peso	5030 gr
Profondità	330 mm
Rack-Mountable	Si
Nr. unità rack	1
CONNETTIVITÀ	
Porta Console	Si
Nr. porte LAN	48 N
Nr. porte Uplink	4
Tipo e velocità porte LAN	RJ-45 10/100/1000/2500
Tipo e velocità porte Uplink	SFP+ 10GbE
DIMENSIONI CON IMBALLO	
Peso con imballo	7,33 kg
Lato A	58 cm
Lato B	50,3 cm
Lato C	9,5 cm