

Enturbo outdoor ap 11ac 2x2 ip67	
Codice	CK469935
EAN	4713361934377
Marca	ENGENIUS
Part number	ENH1350EXT
Storage unit	
Unità di vendita	Cadauno
Confezione	1
Imballaggio	1
Peso (kg)	0.855
Volume (cm ³)	4140
Outdoor CB/AP DBC 11ac Wave2 400+867Mbps 2T2R 4x5dBi RP-SMA GbE PoE.af IP67 Extend your high-speed wireless coverage to the outdoors with the high-powered ENH1350EXT, an 11ac Wave 2, MU-MIMO, Dual-Band Wireless AC1300 Outdoor Access Point. Reaching speeds to 867 Mbps on the 5 GHz and 400 Mbps on the 2.4 GHz frequency band, this feature-rich AP leverages advanced Wi-Fi and Beamforming antenna technology, maximizing performance and increasing outdoor or indoor network capacities. The AP is designed to operate in harsh environmental conditions and includes an IP67-rated weatherproof housing. The ENH1350EXT is easy to install in virtually any location with its included PoE adapter for quick deployment regardless of its proximity to power outlets. The AP is an ideal wireless solution for indoor and outdoor residential and commercial applications. Caratteristiche tecniche:	

Wave 2 MU-MIMO Improves Performance & Expands User Capacities
 IP67-Rated Waterproof & Dustproof Housing Withstands Harsh Environments
 11ac Dual-Radio Speeds to 867 Mbps on 5 GHz; to 400 Mbps on 2.4 GHz
 Beamforming Optimizes Antenna Signal, Reception & Reliability
 Four (4) External 5dbi High-Gain, 360° SMA-Type Antennas
 Band Steering Optimizes Network Traffic Flow ; Fast Roaming Secures Seamless Connections
 Flexible Operation Modes: AP, Client Bridge or WDS
 Quickly View, Monitor & Reconfigure APs Locally or Remotely with EZ Controller Software

SPECIFICHE

Velocità	1300 mbps mbit/s
Marca	ENGENIUS
Numero porte LAN	1 n
Posizionamento	outdoor

CARATTERISTICHE FISICHE

Altezza massima	30 mm
Colore Chassis	Bianco
Formato Chassis	Wall/Celling
Larghezza massima	174 mm
Peso	295 Gr
Profondità massima	111 mm

CARATTERISTICHE TECNICHE

Posizionamento	Outdoor
Unmanaged / Autonomo	Si
Possibilità di essere anche controllato	Si

CONFEZIONE

Software	Quick Installation Guide
Kit e Accessori Vari	Access Point, 2x2.4GHz + 2x5GHz RP-SMA antenna, PoE Adapter (EPA5006GR), Power cord, wall mount screw set, pole clamp, Quick Installation Guide.

CONFORMITÀ

Dichiarazione di Conformità	FCC, IC, CE
-----------------------------	-------------

ALIMENTAZIONE	
Power Supply Frequenza	na Hz
Power Supply Tensione	24 V
Power Supply	POE
Supporto POE 802.3af	Si
CONNETTIVITÀ	
Porta Console	No
Numero porte LAN	1 N
Velocità LAN	1000 Mbps
Connettori porte LAN	RJ-45
WIRELESS	
Banda di frequenza	2,4/5 Ghz
Connettore antenne opzionali	RP-SMA
Velocità Wireless	1300 Mbps Mbps
Wireless Security	Si
Conformità Wireless	IEEE 802.11a/n/ac on 5 GHz, IEEE 802.11b/g/n on 2.4 GHz